

3D seismic survey design – Second edition

Contents

- About the Author xi
- Foreword to the Second Edition xiii
- Foreword to the First Edition xv
- Acknowledgments to the Second Edition xvii
- Acknowledgments to the First Edition xix
- Introduction xxi

Chapter 1 2D symmetric sampling 1

- 1.1 Introduction 1
- 1.2 Shot/receiver and midpoint/offset coordinate systems in two dimensions 1
- 1.3 Symmetric sampling 4
- 1.4 Symmetric sampling versus asymmetric sampling 9
- 1.5 The total stack response 11
- 1.6 Concluding remarks 13

Chapter 2 3D acquisition geometries, their properties, and their sampling 15

- 2.1 Introduction 15
- 2.2 Classes of 3D geometries 16
 - 2.2.1 Examples of various geometries 16
- 2.3 The continuous wavefield 19
 - 2.3.1 The shot/receiver and midpoint/offset coordinate systems 19
 - 2.3.2 3D subsets of the 5D wavefield 19
 - 2.3.2.1 The midpoint line
 - 2.3.2.2 The 3D shot
 - 2.3.2.3 The cross-spread
 - 2.3.2.4 The slanted spread and the zig-spread
 - 2.3.2.5 The COV gather
 - 2.3.2.6 The 3D midpoint
 - 2.3.3 3D subsets and acquisition geometry 23
 - 2.3.3.1 Traveltime contours of 3D subsets
 - 2.3.3.2 Fold of basic subsets
 - 2.3.3.3 Extent of basic subsets
 - 2.3.3.4 Minimal data sets
 - 2.3.3.5 The cross-spread as subset of orthogonal geometry
 - 2.3.3.6 Subsets of zigzag geometry
 - 2.3.4 Fold in 3D seismic data 28
 - 2.3.4.1 Unit cell
 - 2.3.4.2 Fold-of-coverage
 - 2.3.4.3 Illumination fold
 - 2.3.4.4 Image fold
 - 2.4 Sampling the continuous wavefield 31
 - 2.4.1 Binning 31
 - 2.4.2 Sampling and the unit cell 32
 - 2.4.3 Aspect ratios 33
 - 2.4.4 Spatial continuity 34
 - 2.4.5 3D symmetric sampling 34

| | |
|---|----|
| 2.4.6 Line geometries | 35 |
| 2.4.6.1 Parallel geometry | |
| 2.4.6.2 Orthogonal geometry | |
| 2.4.6.3 Zigzag geometry | |
| 2.4.7 Areal geometry | 40 |
| 2.5 Pseudo-COV gathers | 41 |
| 2.5.1 Introduction | 41 |
| 2.5.2 Offset-vector tiles | 41 |
| 2.5.3 Construction of pseudo-COV gathers | 42 |
| 2.5.4 Example of OVTs in 64-fold regular geometry | 44 |
| 2.5.5 Reciprocal OVTs | 45 |
| 2.5.6 A measure of spatial discontinuity | 46 |
| 2.5.7 A plethora of OVT gathers | 47 |
| 2.6 Application to prestack processing | 47 |
| 2.6.1 Introduction | 47 |
| 2.6.2 Noise removal | 48 |
| 2.6.3 Interpolation and regularization | 50 |
| 2.6.4 Muting | 51 |
| 2.6.5 First-break picking | 51 |
| 2.6.6 Nearest-neighbor correlations | 52 |
| 2.6.7 Residual statics | 52 |
| 2.6.8 Velocity analysis | 52 |
| 2.6.9 Multiple suppression | 54 |
| 2.6.10 Amplitude variation with offset | 55 |
| 2.6.10.1 Nears, mids, and fars | |
| 2.6.10.2 AVO measurement in bins or in unit cells | |
| 2.6.11 Amplitude variation with azimuth | 57 |
| 2.7 Conclusions | 57 |

Chapter 3 Noise suppression 59

| | |
|---|----|
| 3.1 Introduction | 59 |
| 3.2 Properties of low-velocity noise | 59 |
| 3.2.1 Direct waves | 59 |
| 3.2.2 Scattered waves | 59 |
| 3.2.2.1 Point scatterer | |
| 3.2.2.2 Line scatterer | |
| 3.3 Shot and receiver arrays in 3D data acquisition | 65 |
| 3.3.1 Introduction | 65 |
| 3.3.2 Effect of linear array on noise | 65 |
| 3.3.3 Effect of linear array on signal | 68 |
| 3.3.3.1 Introduction | |
| 3.3.3.2 Intra-array statics | |
| 3.3.3.3 Length of array | |
| 3.3.3.4 Azimuthal efect | |
| 3.3.4 Direct wave noise suppression | 70 |
| 3.3.5 Scattered-wave noise suppression | 71 |
| 3.3.6 Analysis of various array combinations | 72 |
| 3.3.7 Discussion | 76 |
| 3.4 Stack responses | 77 |
| 3.4.1 Introduction | 77 |
| 3.4.2 The 2D stack response | 77 |
| 3.4.3 Multiple suppression by stacking | 77 |

- 3.4.3.1 Multiples with small differential moveout
- 3.4.3.2 Multiples with large differential moveout
- 3.4.4 3D stack responses 80
- 3.4.5 Discussion 84

Chapter 4 Guidelines for design of 3D geometry on land 87

- 4.1 Introduction 87
 - 4.1.1 Spatial continuity 87
 - 4.1.2 Regular geometry 88
 - 4.1.3 Geophysical requirements/constraints 88
 - 4.1.4 General recipe for 3D survey design 88
- 4.2 Preparations 89
 - 4.2.1 Objective of survey 89
 - 4.2.2 Know your problem 89
- 4.3 The choice of geometry 90
 - 4.3.1 Parallel geometry versus orthogonal geometry 90
 - 4.3.2 Zigzag geometry versus orthogonal geometry 91
 - 4.3.3 Slanted geometry versus orthogonal geometry 92
 - 4.3.4 Comparison of sampled minimal data sets of crossed-array geometries 92
 - 4.3.5 Areal geometry 92
 - 4.3.6 Hybrid geometry 94
 - 4.3.7 Target-oriented geometries 95
- 4.4 Selecting the main geometry parameters 96
 - 4.4.1 Establish representative velocity function 96
 - 4.4.2 Identify main targets 96
 - 4.4.3 Resolution requirements and maximum frequency 96
 - 4.4.4 Establish maximum dip angle in each target 99
 - 4.4.5 Establish spatial sampling intervals 99
 - 4.4.5.1 Various spatial sampling intervals
 - 4.4.5.2 Single-point acquisition versus array-based acquisition
 - 4.4.5.3 Event-oriented sampling intervals
 - 4.4.5.4 Statics and spatial sampling
 - 4.4.5.5 Noise suppression and sampling
 - 4.4.5.6 Discussion on spatial sampling
 - 4.4.6 Establish maximum stretch factor and mute function 104
 - 4.4.6.1 The NMO stretch factor
 - 4.4.6.2 The maximum stretch factor and the mute function
 - 4.4.6.3 Average stretch factor
 - 4.4.6.4 AVO and maximum stretch factor
 - 4.4.7 Establish required fold in each target 107
 - 4.4.7.1 Fold as a dependent or independent parameter
 - 4.4.7.2 Average fold
 - 4.4.7.3 How to determine desired or required fold
 - 4.4.8 Determine line intervals 110
 - 4.4.9 Determine maximum offset 111
 - 4.4.10 Other geometry parameters 112
 - 4.4.11 Harmonizing all requirements 112
- 4.5 Implementing the nominal geometry 113
 - 4.5.1 Zippers 114
 - 4.5.2 Templates 114
 - 4.5.2.1 One-line roll
 - 4.5.2.2 Sources outside template

| | |
|---------|--|
| 4.5.2.3 | Full-swath roll |
| 4.5.2.4 | Multi-line roll with extra receiver lines |
| 4.5.2.5 | Superspread |
| 4.5.2.6 | Multiline roll without extra receiver lines |
| 4.5.3 | The survey grid and the survey area 121 |
| 4.5.3.1 | Determine migration distance |
| 4.5.3.2 | Determine radius of zone of influence |
| 4.5.4 | Dealing with obstacles 123 |
| 4.5.5 | Source selection 127 |
| 4.5.5.1 | Source types |
| 4.5.5.2 | Source strength |
| 4.5.5.3 | The need for low frequencies |
| 4.5.5.4 | Use of different sources in one survey |
| 4.5.5.5 | Simultaneous sources |
| 4.6 | Testing 133 |
| 4.7 | Discussion 134 |
| 4.7.1 | Attribute analysis 134 |
| 4.7.2 | Model-based survey design 134 |
| 4.7.3 | Acquisition footprint 140 |
| 4.7.4 | Random sampling 140 |
| 4.8 | What to do and not to do in 3D survey design 141 |

Chapter 5 Marine seismic data acquisition 143

| | |
|----------|---|
| 5.1 | Introduction 143 |
| 5.1.1 | Air-gun arrays 144 |
| 5.2 | Geometry imprint 144 |
| 5.3 | Streamer acquisition 146 |
| 5.3.1 | Introduction 146 |
| 5.3.2 | Multisource multistreamer configurations 146 |
| 5.3.3 | Crossline-offset variation 147 |
| 5.3.4 | Source interval, number of sources, and fold 149 |
| 5.3.5 | Inline bin size and crossline bin size 149 |
| 5.3.6 | Offset-vector-tile gathers in streamer acquisition 150 |
| 5.3.7 | Effects of spatial discontinuity in marine streamer acquisition 151 |
| 5.3.7.1 | Illumination effects |
| 5.3.7.2 | Azimuthal anisotropy |
| 5.3.7.3 | Reducing spatial discontinuities |
| 5.3.7.4 | Infill shooting |
| 5.3.7.5 | Undersampling |
| 5.3.8 | Maximum offset 160 |
| 5.3.9 | Depth of sources and streamers 161 |
| 5.3.9.1 | Cable noise |
| 5.3.9.2 | Ghost effect |
| 5.3.9.3 | Absorption |
| 5.3.10 | Over/under technique 164 |
| 5.3.11 | Multicomponent streamer 164 |
| 5.3.11.1 | Dual-sensor streamer |
| 5.3.11.2 | Quad-sensor streamer |
| 5.3.12 | Variable-depth streamer 167 |
| 5.3.13 | Shooting direction 167 |
| 5.3.13.1 | Dip/strike decision |
| 5.3.14 | Multiazimuth acquisition 169 |

| | |
|---|-----|
| 5.3.15 Wide-azimuth acquisition | 172 |
| 5.3.15.1 Introduction | |
| 5.3.15.2 Characteristics of wide-azimuth towed streamer acquisition | |
| 5.3.15.3 Parallel or areal geometry? | |
| 5.3.15.4 Compromises in areal WATS | |
| Binsize | |
| Number of sources | |
| Crossline roll | |
| Number of boat passes required for each source track | |
| Maximum offset | |
| Edge effects | |
| Feathering aspects | |
| Summary | |
| 5.3.15.5 Other areal WATS configurations | |
| 5.3.15.6 Simultaneous sources helpful for areal WATS? | |
| 5.3.15.7 Rich azimuth (RAZ) | |
| 5.3.15.8 Coil shooting | |
| 5.3.15.9 Zigzag WATS | |
| 5.3.16 Operational aspects | 186 |
| 5.4 Stationary-receiver techniques | 187 |
| 5.4.1 Introduction | 187 |
| 5.4.2 Some history | 188 |
| 5.4.2.1 Vertical hydrophone cable (VHC) | |
| 5.4.3.2 SUMIC | |
| 5.4.3 Source array | 189 |
| 5.4.4 Coupling issues | 189 |
| 5.4.5 Noise at the sea bottom | 189 |
| 5.4.6 Dual-sensor application | 190 |
| 5.4.7 OBC | 191 |
| 5.4.7.1 Implementation aspects | |
| 5.4.7.2 Geometries for OBC acquisition | |
| 5.4.7.3 OBC acquisition with buried cables | |
| 5.4.8 Ocean-bottom seismometers | 195 |
| 5.4.9 Transition-zone acquisition | 197 |
| 5.5 Time interval between shots and source strength | 198 |
| 5.6 Time-lapse acquisition | 198 |
| 5.6.1 Introduction and objective | 198 |
| 5.6.2 Measures of nonrepeatability | 199 |
| 5.6.3 Causes of nonrepeatability | 201 |
| 5.6.4 Ways to improve repeatability | 202 |
| 5.7 Discussion | 204 |

Chapter 6 Converted waves: Properties and 3D survey design 207

| | |
|---|-----|
| 6.1 Introduction | 207 |
| 6.2 Properties of the PS-wavefield | 208 |
| 6.2.1 Traveltime surfaces and apparent velocity | 208 |
| 6.2.2 Illumination | 209 |
| 6.2.3 Imaging | 210 |
| 6.2.4 Resolution | 212 |
| 6.2.5 NMO stretch in PS-waves | 218 |
| 6.2.6 Shear-wave splitting | 218 |
| 6.3 3D survey design for PS-waves | 219 |

| | | |
|---------|--|-----|
| 6.3.1 | Choice of geometry | 219 |
| 6.3.1.1 | Orthogonal geometry | |
| 6.3.1.2 | Parallel geometry | |
| 6.3.1.3 | Areal geometry | |
| 6.3.1.4 | Parallel versus orthogonal geometry and areal geometry | |
| 6.3.2 | Sampling | 225 |
| 6.4 | Processing considerations | 225 |
| 6.5 | Conclusions and recommendations | 226 |

Chapter 7 Some lowfold data examples 229

| | | |
|-------|--|-----|
| 7.1 | Introduction | 229 |
| 7.2 | 3D microspread | 229 |
| 7.2.1 | Introduction | 229 |
| 7.2.2 | Acquisition parameters of 3D microspread | 229 |
| 7.2.3 | Cross sections and time slices | 229 |
| 7.2.4 | $f-k$ filtering results | 231 |
| 7.2.5 | Discussion | 232 |
| 7.3 | Nigeria 3D test geometry results | 234 |
| 7.3.1 | Introduction | 234 |
| 7.3.2 | Acquisition geometry | 235 |
| 7.3.3 | Some processing results | 238 |
| 7.3.4 | Interpretation results | 238 |
| 7.3.5 | Discussion | 238 |
| 7.4 | Prestack migration of lowfold data | 241 |
| 7.4.1 | Introduction | 241 |
| 7.4.2 | Migration of a single cross-spread | 242 |
| 7.4.3 | Lowfold prestack migration | 243 |
| 7.4.4 | More lowfold migration results | 244 |
| 7.4.5 | Discussion | 246 |

Chapter 8 Factors affecting spatial resolution 247

| | | |
|-------|--|-----|
| 8.1 | Introduction | 247 |
| 8.2 | Spatial resolution formulas | 248 |
| 8.2.1 | Spatial resolution — The link with migration/inversion | 248 |
| 8.2.2 | Spatial resolution formulas for constant velocity | 249 |
| 8.3 | Spatial resolution measurements | 251 |
| 8.3.1 | Procedure for resolution analysis | 251 |
| 8.3.2 | 2D resolution in the zero-offset model | 252 |
| 8.3.3 | 2D resolution in the offset model | 253 |
| 8.3.4 | Asymmetric aperture | 254 |
| 8.3.5 | 3D spatial resolution | 255 |
| 8.3.6 | Sampling and spatial resolution | 257 |
| 8.3.7 | Sampling and migration noise | 257 |
| 8.3.8 | Bin fractionation | 258 |
| 8.3.9 | Fold and spatial resolution | 259 |
| 8.4 | Discussion | 260 |
| 8.5 | Conclusions | 261 |

Chapter 9 DMO 263

| | | |
|-----|--|-----|
| 9.1 | Introduction | 263 |
| 9.2 | DMO in arbitrary 3D acquisition geometries | 264 |

| | | |
|-------|--|-----|
| 9.2.1 | The time of a DMO-corrected event | 264 |
| 9.2.2 | Contributing traces in cross-spread | 265 |
| 9.2.3 | DMO-corrected time in the cross-spread | 266 |
| 9.2.4 | Extension to other geometries | 266 |
| 9.3 | Results with synthetic data | 267 |
| 9.4 | New DMO programs | 268 |
| 9.5 | DMO in OVT gathers | 269 |
| 9.6 | Conclusion | 269 |

Chapter 10 Prestack migration 271

| | | |
|----------|--|-----|
| 10.1 | Introduction | 271 |
| 10.2 | Migration basics | 271 |
| 10.2.1 | The purpose of migration | 271 |
| 10.2.2 | Migration as a two-step process | 273 |
| 10.3 | Fresnel zone and zone of influence | 275 |
| 10.3.1 | Modeling | 275 |
| 10.3.2 | Migration | 275 |
| 10.4 | Experiments with synthetic data | 278 |
| 10.4.1 | Description of model experiments | 278 |
| 10.4.2 | Prestack migration with minimal data sets | 278 |
| 10.4.3 | Prestack migration with pseudo-COV gathers | 280 |
| 10.4.3.1 | Parallel geometry | |
| 10.4.3.2 | Orthogonal geometry | |
| 10.4.3.3 | Intermezzo: Imaging test with singlefold gathers | |
| 10.4.3.4 | Illumination and imaging in orthogonal geometry | |
| 10.4.3.5 | Areal geometry | |
| 10.4.3.6 | Irregular geometries | |
| 10.5 | Discussion | 290 |

Appendix A Sampling and aliasing 293

Appendix B Aperture for sampled wavefields 297

| | | |
|-----|------------------------------|-----|
| B.1 | Introduction | 297 |
| B.2 | Continuous aperture function | 297 |
| B.3 | Discrete aperture function | 297 |
| B.4 | Conclusions | 299 |

Appendix C Useful formulas in 3D seismic survey design 301

| | | |
|-----|----------------------------|-----|
| C.1 | Introduction | 301 |
| C.2 | Algorithm for average_fold | 302 |

Appendix D Fold requirement of 3D survey 303

Appendix E Nomenclature 307

References 311

Index 333