

Index

- absolute-offset distribution, 33, 51
 - absolute-offset gather, 53, 280, 282, 288
 - absolute-offset range, 45, 52, 53, 55, 57, 119, 281, 285
 - absorbing boundary conditions, 225
 - absorption, 162, 163–164, 217–218, 219, 225
 - accelerated weight drop (AWD), 130
 - access to survey area, 35, 90, 127, 132, 160, 235
 - acoustic impedance, 131, 144, 198, 248
 - acoustic positioning, 164
 - Acquisition Design Wizard, 113
 - acquisition footprint/imprint, 28, 51, 57, 92, 118, 119, 121, 140–142, 144, 158, 193, 290 (*see also* geometry imprint)
 - crossline roll, 28, 117, 119, 145, 158
 - less serious for smaller line intervals, 140, 141, 146
 - minimization by true-amplitude migration, 155, 280, 285, 288, 290
 - multiline roll, 121, 142
 - periodicity, 28, 140, 145
 - reduction by offset-vector oriented muting, 51, 140
 - striping (*see* striping)
 - acquisition lines, straight or smoothly curved, 123–124, 142
 - adequate Nyquist wavenumber, 5
 - adequate sampling interval, 5–7, 13, 35, 40, 99, 100
 - air-gun array, 127, 144, 146, 149, 161, 166, 178, 180, 189, 195, 203, 227
 - in transition zone, 197, 235
 - air-gun and dynamite sources in same survey, 132, 238, 239
 - Alabama, offshore, 197
 - Algeria, orthogonal versus parallel geometry, 90, 118, 119
 - algorithm for average fold, 302
 - alias-free (spatial) sampling, proper sampling, 2, 5, 7, 16, 34, 35, 39, 40, 64, 68, 69, 91, 94, 102, 103, 225, 229, 230, 267, 293–295, 301
 - and resolution, 99, 248, 278
 - and spatial continuity, 34, 87, 88
 - and maximum wavenumber, 2, 5, 6, 103
 - condition for, 5, 19, 293
 - defined*, 2, 19, 35
 - for migration, 271, 278, 279, 288
 - in high-velocity area, 64
 - of all four spatial coordinates, 16, 35, 99
 - of basic subsets, of two spatial coordinates, 34, 35, 39, 40, 42, 57, 87, 88, 91, 94, 110, 220, 259, 264–267, 288, 293
 - of events of interest, 99, 102
 - of *N*-dimensional wavefield, 295
 - of PS-waves, 225
 - of the noise, 60, 68, 230
 - of the signal, of desired wavefield, 7, 69, 99, 102, 103, 140, 230, 258, 264, 279
 - of wavefield of shot record, 229
 - aliasing, 5, 33, 92, 102, 103, 230, 293–295, 301
 - and random sampling, 140
 - in common-offset gathers, 180
 - of migration operator, 173, 274
 - of multiples, 80, 82, 149
 - of signal, 102, 103, 163, 192
 - reduction by arrays, 7, 35, 38, 39, 67, 68
 - spatial, 5, 7, 33, 92, 102, 103, 243, 274
 - temporal, 293, 294
 - aliasing noise, 35
 - alias peak/band in stack response, 77, 80, 82, 258
 - Amazon rain forest, Peru, 244
 - ambient noise, 50, 100, 127, 130, 164, 198, 202, 261
 - and deep tow, 164
 - and high frequencies, 130
 - and source strength, 127, 130, 198
 - array effect, 100
 - property, 50
 - amplitude spectrum (*see* frequency spectrum)
 - amplitude variation with azimuth (AVAz), 48, 57, 155, 158
 - amplitude variation with offset (AVO), 55–57 (*see also* AVO analysis)
 - Andrew field, North Sea, 94
 - angle of incidence (*see* reflection angle)
 - antialias filter in migration, 102, 274
 - antialiasing by arrays, 7, 11, 35, 38, 39, 66, 72
 - antiparallel acquisition, 148, 151–153, 155–159, 177, 179, 281
 - aperture for sampled wavefields, 297–299
 - application to array length, 11, 297
 - application to crossline dimension of template, 26
 - application to spread length, 28, 29, 257
 - apex area of scattered wave, 60, 62–64
 - apparent dip, 54, 55, 264, 265, 293
 - apparent slowness, 60
 - apparent velocity, 5, 35, 39, 48, 59, 60, 62, 65, 66, 68, 80, 82, 102, 103, 149, 192, 208, 232, 258, 294, 295, 301
 - in zig- and zag-spreads, 91
 - minimum, 5, 65, 68, 100, 102, 225
 - of diffractions, 102, 225
 - of direct wave, 59
 - of multiple, 80, 82
 - of noise, of ground roll, 35, 39, 48, 59, 60, 62, 65, 66, 94, 149, 225, 293, 294
 - of PS-wave, 208
 - of signal, 62, 65, 66, 68
 - of S-wave, 230
 - apparent wavelength, 230
 - apparent wavenumber, 69
 - Arabian Gulf, 198
 - areal array, 38, 39, 70, 71, 72, 77, 233 (*see also* array)
 - advantage over linear array, 39, 72
 - dimension, 40
 - suppression of scattered energy, 72, 77, 233
 - areal geometry, 16–18, 20, 34, 40–41, 92–94, 144, 223–227
 - alternative to hybrid geometry, 94
 - and analysis of azimuth-dependent effects, 223
 - and desert areas, 93
 - and scattered ground roll, 77, 93
 - and WATS, 172, 175–180
 - aspect ratios, 33, 34
 - basic subset, 21
 - equivalence with orthogonal geometry, 40–41, 176
 - expense on land relative to offshore, 93
 - hexagonal sampling, 28, 34, 40–41, 196, 197, 295
 - OVTs, 46, 47, 151, 285, 288–290
 - type 1 and type 2, 16, 40, 93
 - unit cell, 28
- array, field array, 7–13, 15, 35–40, 59, 65–77
 - and 2D fold versus 3D fold, 109
 - and velocity filtering, 67, 68
 - areal, 35, 38, 39, 70–76, 233
 - asymmetric sampling, 9, 10
 - azimuthal effect, 69, 70
 - circular, 69, 72, 73, 95

- dynamite, 128, 235
 effect on noise, 65–68
 effect on signal, 68–70
 in areal geometry, 40, 93, 95
 in orthogonal geometry, 38, 39
 in parallel geometry, 35
 intra-array statics, 7, 68, 69, 101, 103, 229
 length, 7, 9, 11, 68, 69, 297–299
 linear, 7, 35, 38, 65–72, 76, 77, 120, 299
 requirements, 35
 resampling operator and antialias filter, 7, 11, 35, 38, 40, 66, 68
 response (*see* array response)
 shot and receiver array combination, 7, 8, 9, 38, 39, 65, 69, 71–76
 staggered rather than linear, 120
 weighted, 7
- array-based acquisition, 100, 101, 103, 117, 232
 resolution at depth, 101
 sampling strategy, 101
- array-based symmetric sampling, 7, 8, 13, 35, 100
- array elements, 7, 8, 65–68, 70–72, 76, 129, 299
 formula for interval, 66
 interval, 7, 11, 15, 65, 66, 71, 297
 regular uninterrupted sampling, 7
 required number, 67
- array response, 11, 12, 65–77, 161, 298, 299
 azimuthal effect, 69, 70, 72
 central passband, 11, 70
 contour plots, 71, 73–75
 first notch, 7, 11, 13, 65, 66, 68, 76, 77, 95
 formula, 11, 70, 71
 ideal, 11
 NMO effect, 11
 optimal, 76
 side lobes, 66, 67, 161
 small offsets, 71
 suppression band, 66
- aspect ratio, 26, 33, 34, 38
 and average stretch factor, 106
 and geophysical requirements, 88
 of bin, 33, 34
 of cross-spread, 26, 33, 36, 37, 84, 142
 of geometry, 33, 34, 173
 of unit cell, 33, 34, 37, 38, 111
 wide versus narrow geometry, 26, 36, 38, 82, 84, 237
- asymmetric sampling, 9, 10, 12, 92, 112, 225, 243
 in zigzag and slanted geometry, 91, 92
- Atlantis survey, Gulf of Mexico, 40, 196
- attribute analysis of acquired data, 158, 238, 239
- attributes of geometry, spatial, 27, 87, 92, 117, 134–138, 139, 265
 attribute analysis, 87, 134–138, 139
 attribute maps, 121, 241
- AVAz (*see* amplitude variation with azimuth)
- average fold, 38, 104, 108
 algorithm, 302
 coil shooting, 183, 185
 formula, 108, 183
- average stretch factor, 99, 106–107, 301
 for 2D and wide 3D data, 106–107
- AVO analysis, 10, 44, 55–57, 107, 111, 112, 132, 169, 199
 azimuth-dependent, 111
 bin-oriented approach, 56
 dip versus strike shooting, 169
 nears, mids, and fars, 55, 56
 of array-based data, 69
 of data acquired with simultaneous shooting, 132
 offset requirements, 107, 112
 orthogonal geometry OBC data, 44
 unit-cell-oriented approach, 56–57
- AWD (accelerated weight drop), 130
- Azeri field, Caspian Sea, 94, 192
- azimuthal anisotropy, 51, 55, 57, 58, 88, 112, 122, 155, 158, 160, 193, 207, 226
 analysis, 51, 55, 57, 88, 193, 207, 226
 correction, 57, 58, 160
 design requirements, 88, 111, 112, 122, 226
 effect on MS/MS acquisition, 155, 158
- azimuth-dependent effects, 57, 91, 172, 223, 224, 225
- bandwidth, 15, 76, 96, 108, 109, 127, 129, 131–132, 161, 164–167, 197, 248, 251 (*see also* maximum frequency)
 and fold, 108, 109
 need for low frequencies, 131–132
 of noise, 76, 129
 of source, 15, 127, 129, 130
 of streamer data, 161, 163, 164–167
 of TZ-data, 197
- baseline survey, 196, 198, 199, 200, 203, 204
- basic sampling interval, 5, 6, 35, 40, 65, 99–101, 103
- basic signal sampling interval, 6, 35, 40, 65, 91, 99–101, 103
- basic subset, 19, 21–23, 25, 28, 35, 40, 92, 94, 134, 175, 229
 fold, 25, 28, 29
 extent, 25, 34, 35, 46, 58
 sampling, 35, 57
- Beylkin's formula for spatial resolution, 247, 248, 249, 255, 256, 260, 261
 limits on achievable resolution, 260
- bin center, 32, 91, 124, 269
- bin fractionation, 258–260
- bin grid, 31, 88
- binning, 31–32, 44, 91, 207, 247
- bin size, 30–32, 49, 88, 90, 102, 108, 112, 113, 147, 149, 164, 169, 173, 174, 178, 183, 210, 227, 247, 301, 303
 and fold, 30
 and 3D fold from 2D fold, 108, 109, 301, 303
 crossline (*see* crossline bin size)
 inline, 32, 149, 178, 183
 in parallel geometry, 35, 36, 90, 119, 149, 150, 152, 163, 164, 167, 171, 178
 in WATS acquisition, 172–178
 natural, 30, 31, 210, 258
- bin smear (*see* midpoint smear)
- boat/vessel pass, 28, 29, 35, 146, 147, 148, 149, 152, 153, 155, 157, 160, 176, 177, 178, 203, 281
- body waves, 191, 230
- box test, 133, 234
- brick or brick-wall geometry, 18, 27, 82, 92, 133, 141, 219, 234–236, 241
 and spatial continuity, 27, 234
 LMOS, 234, 235
 stack response, 82, 83
- bright spots, 18
- broad frequency band, 130, 131, 161, 164, 166, 255, 275, 276
- Brunei, 118, 197
- bulge waves, 161
- Bullwinkle survey, 169, 170
- buried cables, 19, 94, 144, 189, 194, 195, 203
- buried-sources/buried-receivers technique, 203
- cable-free sampling, 140, 141
- cable noise, 161
- California, 18
- Canada, 35
- Cantarell complex, 196
- carbon dioxide sequestration, 89
- Cartesian offset binning, common (CCOB), 44
- cascaded f - k filter, 10, 36, 48, 49, 232, 234, 240 (*see also* dual-domain filtering)
- case study land acquisition, 234–241
- Caspian Sea, 94, 192
- CCOB (common Cartesian offset binning), 44
- center-spread acquisition (3D), 26, 27, 28, 34, 42, 88, 143, 192
 shots and receivers, 34, 42, 88
 in parallel geometry, 36, 90, 159, 171, 204, 209

- in zigzag and slanted geometry, 27, 114
- center-spread acquisition (2D), 8–11
- center spread versus end on, 9, 143
- checkerboard effect, 11 (*see also* odd/even effect)
- Cheops pyramid, 23
- Chirag-Azeri fields, Caspian Sea, 192
- choice of geometry, 90–95, 193, 219–225
- CIG (common-image gather), 53, 54, 56–58, 271, 274, 281, 282, 285
- circular array, 69, 72–74, 76, 95
- circular cone as travelttime surface, 25, 59, 60, 61, 64, 77, 93
- circular events in time slices, 36, 37, 230
- circular geometry, 19, 95, 181–185, 204
 - coil shooting, 19, 181–185, 204
- circular midpoint area, 37, 106, 238
- circular velocity filter, 59
- circular WATS, 183, 204
- clean image area, 222
 - solution for edge effects of PS-data, 225–226
- closed grid of acquisition lines, 44, 121, 193, 194
- CMP (common midpoint), 1, 3, 9, 10, 15, 20, 22, 23, 28, 32, 53, 77, 80–82, 84, 91, 92, 95, 106, 144, 145, 209
 - offset sampling, 77, 91, 92, 144, 145, 149, 193
- CMP-array response, (stack response), 11
- CMP gather, 4, 9, 15, 54, 84, 91, 106, 145
- COA (common-offset-with-constant-azimuth), 22 (*see also* COV)
- coarse sampling, 16, 34, 35, 65, 68, 94, 95, 104, 140, 142, 164, 169, 172, 175, 183, 190, 194, 227, 247, 248, 257–261, 271, 288
 - compare coarse with dense, 99, 230, 259
 - compensation with arrays, 40, 65, 68, 95, 101, 102
 - compensation with fold, 104, 108, 180, 247, 260
 - compensation with quasi-random sampling, 140
- coherent noise, 10, 60, 79, 91, 125, 201, 230, 232, 236, 258, 302
 - at sea bottom, 189, 190
 - in shot gathers, random in receiver gathers, 132, 161
 - interference, 132
 - vibrator generated, 129
- coherent noise suppression
 - by processing, 161, 169, 302
 - by shot and receiver arrays, 10, 38, 69, 129
 - by stacking, 77, 79, 81, 82
- coil shooting, 19, 139, 143, 161, 181–185, 186, 204
 - fold plots, 182, 184
- Colorado School of Mines, 128
- common-azimuth gather, 21, 22, 27
- common-focal-point matrix, 277
- common-image gather (*see* CIG)
- common-inline-offset gather
 - in parallel geometry, 36, 151, 271
 - in zig- and zagspreads, 27, 28, 39, 92, 93
- common midpoint (*see* CMP)
- common-offset gather, 2, 4, 10, 209, 250, 263, 271
 - in cross-spread, 21, 22
 - in parallel geometry, 149, 172, 180, 209, 261, 263, 280
 - in zig-spread, 27
- common-offset-gather-with-constant-azimuth, 22
- common-offset-range gather, 52, 53
- common-offset-vector gather (*see* COV)
- common-receiver diffraction, 208
- common-receiver gather, 4, 5, 7, 27
 - and interference noise, 132
 - and obstacles, 124–126
 - common-shot-gather look-alike, 90
 - in brick-wall geometry, 141
 - in cross-spread, 21, 36, 38, 39, 50, 123, 132, 190, 229–234
 - in VHC, 188
 - in zig-spread, 27, 39, 91, 93
 - properties, 5
 - travelttime contours, 208
- common-shot diffraction, 208
- common-shot gather, 1, 2, 4, 5, 7, 10, 23, 25, 27
 - in cross-spread, 21, 36, 38, 39, 100, 102, 123, 132, 190, 229–234
- in zig-spread, 39, 91
- symmetric sampling, 7
- travelttime contours, 23, 208
- wavefield properties, 5
- complex geology, 10, 30, 31, 34, 89, 95, 102, 119, 157, 170–172, 219
 - and illumination/imaging, 30, 37, 45, 46, 90, 139, 176, 177, 188
 - and modeling, 134, 139
 - and small sampling intervals, 95, 101, 103, 104
 - and time lapse, 202
- concentric circle survey, 18, 95, 168, 181
- continuous aperture function, 297
- continuous wavefield, 19–31
 - sampling, 31–41
 - 3D subsets, 19–28
 - 3D symmetric sampling, 34–41
- converted waves, 207–227
 - applications, 207
 - processing considerations, 225–226
 - properties of, 208–219
 - resolution, 212–219
 - 3D survey design, 219–227
- coordinate systems, shot/receiver and midpoint/offset, 1–3, 19, 201
- coupling of sensors, 1, 10, 189, 190, 197, 199
- coupling of statics, 29, 52, 90, 117
- COV (common-offset-vector) gather, 20, 22, 23, 24, 25, 35, 36, 41, 45, 59, 151, 220, 221, 225, 226, 255, 271, 277–281
 - alternative name for OVT gather, 43
 - DMO, 266
 - extent, 25, 35, 41
 - impossible to generate in orthogonal geometry, 281
 - PP-resolution, 97–99, 251, 256
 - PS-illumination and imaging, 208–215
 - PS-resolution, 216–217, 223, 226
 - spatial continuity, 47
 - travelttime contours, 23, 24, 208, 209
- crossed-array geometries, 16, 25, 28, 32, 33, 41, 92, 93, 180, 209
- crossline bin size, 32, 183, 301
 - addressed by quad-sensor streamer, 167
 - case study, 149, 150, 164
 - formula in parallel geometry, 36, 147
 - in crossed-array geometries, 32
 - in parallel geometry, 32, 35, 36, 119, 147, 149, 150, 152, 163, 171, 204
 - in WATS acquisition, 173, 175, 176, 177, 178, 180
- crossline fold, 28, 29, 30, 32, 33, 82, 88, 90, 92, 112, 113, 117, 120, 122, 148, 151, 157, 159, 171, 173, 174, 175, 178, 179, 180, 192, 204, 221, 222, 226, 227, 237, 302
 - larger than one for less irregular illumination in MS/MS, 157
- crossline interpolation, 167, 169, 178, 184, 185, 203, 204
- crossline roll, 28, 90, 113, 114, 116, 117, 118, 119, 192
 - in full-patch roll, 193
 - in full-swath roll, 117
 - in marine data acquisition, 28, 148, 151, 155, 157, 158, 171, 173–180
- cross-spread, 16, 17, 20, 21, 22, 23, 24, 26–27, 29, 42, 43, 48, 54, 223, 242, 254, 261, 267
 - and OVTs, 42
 - and template, 26, 27
 - aspect ratio, 26, 33, 36, 37, 84, 142
 - diagnostic display showing surface consistency, 238–239
 - illumination, 43, 285, 287
 - properties, 21, 22, 27
 - PS-illumination and imaging, 209–212
 - resolution, 254, 256, 261
 - single, migration, 242
 - subset of orthogonal geometry, 26–27
 - suitability for DMO, 267
 - 3D subset, 20
 - time slices through, 22, 37, 50, 232
 - travelttime contours, 23, 24, 37, 60, 61, 64–66, 93
 - travelttime contours for PS-waves, 208, 209
- cross-spread geometry, 18, 119, 234, 241

- cross-spread-oriented processing, 48–50, 52, 54–55, 238
cross-spreads supplementing 2D acquisition, 244–245
cumulative fold, 37, 38, 237
C-wave, 207 (*see also* PS-wave)
- data-adaptive filtering, 50, 65
data quality
 2D versus 3D, 108, 305
 and acquisition geometry, 18, 84, 90, 118, 170–172, 177, 187
 and field tests, 133
 and line intervals, 107, 110, 193
 and random sampling, 140, 261
 and station intervals, 69, 99, 142, 163, 261
 and simultaneous shooting, 132, 227
 and type of source, 129, 130
 array-based versus single-sensor acquisition, 101
 dependence on short offsets, 139, 178
 inline versus crossline, 36, 142
 marine streamers, 149, 171, 177, 187, 204
 (near)-surface effects, 10, 89, 103, 197, 246
 obstacles, 187
 of final data (image quality), 35, 36, 110, 122, 132, 177, 238
 of processing results, 51, 56, 79, 160, 224
 of processed C-waves, 224, 225
 of single-fold gathers, 34, 51, 176, 263
 prediction by modeling, 139
 random geometry, 184
 shooting direction, 169
 wide-azimuth, 172, 178, 180, 204
 wide versus narrow geometry, 142, 238
- decimation tests, 110, 113, 134
deghosting, 162, 164–167
demigration, 50, 54
dense sampling, 1, 7, 13, 16, 18, 35, 47, 50, 59, 63, 140, 149, 178, 180, 183, 190, 191, 194, 225, 227, 234, 249, 259, 261, 273, 274, 275
 areal geometry, 16, 18, 21, 34, 40, 47, 92, 93, 144, 172, 175, 178, 180, 196, 221, 289, 290
 coarse versus dense, 99, 258
 hybrid geometry, 19, 94, 117, 194, 195
 line geometry, 16, 50, 59, 99, 100, 150, 164, 183, 209, 219, 221, 222, 234, 259
 of offset, 15, 77, 92, 183
 regular versus random, 258
- depth coordinate, 18, 188
deserts, 18, 39, 90, 91, 93, 103, 120
 and areal geometry, 93
 and parallel geometry, 90
 and superspread, 120
 and zigzag geometry, 18, 39, 91
- differential feathering, 41, 149, 153, 168, 170
differential moveout, multiples with, 37, 54, 79, 83, 84, 91, 111, 149
 large, 54, 79, 91, 149
 small, 37, 54, 79, 83, 84, 91, 111
- diffracted multiples, 37, 89, 170, 171, 172
diffraction flattening, 211, 214, 243, 257, 273, 274, 279, 282
diffraction-flattened gather, 242, 257, 273, 274, 279, 281, 282
 depth contours, 211, 214, 279, 282, 283
 real data example, 274
 time slices, 243, 284
- diffraction stack, 272–274, 303
diffraction tomography, 247
diffraction traveltime surface (*see* traveltime contour/surface)
diffraction image, cross-shaped, 252, 254
Digiseis system, 18
diodic effect, 209
dip filtering, 226
dip moveout (*see* DMO)
dip or strike acquisition/shooting, 9, 143, 151–157, 168–170, 265, 281
 downdip, 9, 151–153, 155–157, 159, 217, 226, 281, 285
 strike, 143, 156, 168, 169
 updip, 9, 151–153, 155, 156, 159, 209, 226, 281
- dip/strike decision, 167–169
direct wave/arrival, 59, 60, 62, 70–71, 76, 81, 99, 189, 195
discrete aperture function, 297
discrete spatial Fourier transform, 11
distance-separated simultaneous sweeping technique (*see* DS3)
DMO, (dip moveout), 25, 32, 50, 52–53, 56, 91, 92, 111, 118, 124, 154, 155, 172, 238, 263–270
 and cross-spread, 263, 265–266, 267–269
 and featherless MS/MS configurations, 266
 and long offsets, 269
 and removal of reflection-point dispersal, 264, 265
 and MDSs, 266, 269
 and wide-azimuth data, 263, 270
 applied to land seismic data, 263
 applied to singlefold data, 263
 converts, NMO-corrected data to zero-offset data, 263
 correction factor, 265, 267
 criterion for successful, 265
 in arbitrary 3D acquisition geometries, 263–267
 in OVT gathers, 269
 locus of contributing midpoints, 265–267, 269
 new DMO programs, 268–269
 synthetic data, results with, 267–268
- DMO-corrected event/time, 264–267
DMO-correction traces, 91, 268, 269
DMO equalization technique, 154, 155, 266, 269
DMO panel, 264–266, 268, 270
DMO shift, 266, 267, 268
dominant frequency, 69, 123, 302
double zigzag geometry, 18, 82–84, 91–92
downtime, 117
Draugen time-lapse analysis results, offshore Norway, 199, 200
DS3, distance-separated simultaneous sweeping, 40, 95, 120, 132, 133
dual-coil shooting, 161, 181
dual-domain filtering, 238, 240 (*see also* cascaded *f-k* filter)
dual-hydrophone stationary-receiver technique, 18, 187, 188, 197
dual-sensor streamer, 164–166, 167, 186
dual-sensor technique, 144, 187, 188, 190–191, 192, 197
 illustration of principle, 165
- duplex wave, 95
dynamite source, 9, 10, 19, 69, 114, 117, 127–130, 132, 140, 197, 235, 238
 array, 69, 128, 235
 depth and charge tests, 128–129
 expense, 128, 140
 in full-swath roll, 117
 jittered sampling, 140
 relation charge size and frequency content, 128
 shallow arrays versus single deep holes, 128
 single deep hole, 9, 10, 69, 128, 235
- dynamite versus vibroseis acquisition, 129, 130
- edge effects, 25, 31, 123, 172, 176, 177, 210, 220, 225–226, 238, 242, 244, 246, 267, 269, 279, 280, 283, 288, 291
 displayed, 156, 157, 159, 212, 213, 222, 241, 242, 278, 280–282, 286–291
 in PS-data acquisition, 210–212, 220, 222, 223, 225, 226
 mitigation, 31, 45, 46, 176, 225, 226, 288
- edge management, 121–123
effective fold, 37, 51 (*see also* average fold)
effective length of sampled range is $n\Delta x$, 299
 aperture, 257
 array, 72, 74, 101, 120, 129
 spread length, 257
 width, 100
- effective length of wavelet (dependent on amplitudes), 260
Egypt, 170
Ekofisk field, 195
electromagnetic thumper, 130
elemental traces, 7

- elevation variations, 68, 69, 117, 124
 location of shot lines, 124
 station interval, 117
- end-on geometry, 9, 10, 143 (*see also* off-end geometry)
- equation of motion, 167
- equivalence conditions, 40
- equivalent geometries, 39, 40, 91, 92, 142, 176, 186, 223, 234, 301
 OVT in zig-spread and in cross-spread, 92
- event-oriented sampling interval, 99, 102
- excess traces in template implementations, 117, 118, 119, 140, 186, 193
- fat receiver lines, 100, 101
- faults, 96, 99, 104, 168, 238, 241
 illustration in cross spread, 241
- feather-correction procedure, 180
- feathered strings and perpendicular strings, 74
- feathering, 25, 41, 90, 143, 144, 146, 149, 153, 154, 160, 161, 167, 168, 170, 172, 177, 178, 181, 183, 192, 201, 203, 204, 267, 281, 290
 and coil shooting, 181, 183, 204
 and DMO, 266
 and geometry imprint, 144, 146
 and illumination, 90, 143, 153, 154, 204, 281, 290
 and infill shooting, 149, 160–161
 and repeatability, 201, 203
 and WAZ, 177–178
 differential, 41, 149, 153, 168, 170
 steerable streamers, 143, 160, 161
- feathering angle, 149, 160, 161
- Fermat's principle, 207
- fiber optic in LoFS, 195
- field array (*see* array)
- first break, 230, 231, 232, 238
- first-break picking, 51–52
- 5D prestack wavefield, 16, 18, 19, 20, 23, 31, 34
 expense of proper sampling, 35, 57
 sampling, 31–41
 subsets, 19–23
- f-k* diagram, *f-k* spectrum, 4, 80, 81, 100, 230, 231, 293, 294
- f-k* domain, 60, 67, 294
- f-k* filtering, 13, 49, 91, 101, 125, 231–234, 238, 240
 cascaded/dual-domain, 49, 238, 240
- f-k-k* domain, 103
- f-k_x-k_y* filter, 48
- f-k* spectrum (*see f-k* diagram)
- flexibin, 258, 259
- flower-plot analysis, 139
- flying nodes project, 205
- Foinaven field, 195
- fold (fold of coverage), 25, 28–30, 107–110, 260, 261
 and illumination fold, 28, 30
 and image fold, 28, 30, 31
 and line intervals, 30
 and migration artifacts, 108
 and overlapping midpoint areas, 25, 28–31, 32, 88, 139, 210, 220, 224, 243
 and recorded noise, 108
 and resolution of coarsely sampled data, 259–260
 average (*see* average fold)
 constant fold in time slices, 51
 crossline (*see* crossline fold)
 cumulative, 37, 38, 237
defined, 28, 29
 dependent or independent parameter, 107
 even fold or odd fold, 32, 33
 field versus nominal, 117
 general formula, 29
 increase, and resolution, 108, 109, 261
 increase, and S/N, 108
 independent of station intervals in crossed-array geometries, 29, 30
 inline (*see* inline fold)
- number of overlapping midpoint areas, 28, 29
 number of traces per bin, 28, 29
 required, 89, 96, 107–110, 133, 185, 246, 303–305
 taper zone, 121, 122
 3D fold from 2D fold, 108–109, 303–305
 3D test data and decimation tests, 110
 total fold, 29
 2D fold, 28, 29
- fold buildup, 37, 112, 113, 121, 237
 and line intervals, 237
 in taper zone, 112, 113, 121, 122
 wide versus narrow geometry, 37, 38
- fold plot, 44, 119, 121, 122, 135–138, 182, 183, 184, 194, 281
- formulas useful in 3D seismic survey design, 301–302
- formulas for geometry parameters, 112, 113
- 4C (four-component) acquisition, 94, 144, 187, 189, 195, 196, 207, 223
 applications, 207
defined, 144
- 4C sensor, 189
- 4D acquisition, 178, 195, 198 (*see also* time-lapse acquisition)
- Fourier transform, 2, 3, 184, 298
- fracture density, 89, 207, 219
- fracture-detection analysis, 207
- fracture orientation, 89, 207, 219, 224
- frequency spectrum, amplitude spectrum, 109, 129, 130, 161, 162, 164–166, 255, 278, 293
- frequency-wavenumber (*f-k*) spectrum (*see f-k* diagram)
- Fresnel aperture, 275, 303
- Fresnel zone, 160, 271, 274, 275–278, 290
 and infill strategy, 160
 and zone of influence (ZOI), difference, 275–278, 290
 first, 275
 monochromatic waves, and broadband data, 275
 radius of first zone, 275, 276
- full fold, 121, 122, 184 (*see also* total fold)
 distance to, 112, 113, 121
- fullfold area, 29, 44, 45, 88, 111, 113, 114, 115, 121, 122, 134, 151, 182, 183, 193, 194
 for pilot survey, 113, 134
 limited by shortest acquisition lines, 193, 194
 of zipper, 114, 115
- fullfold bin, 47, 183
- full-patch roll, 114, 192–195
- full-resolution recording, 9
- full-swath roll, 114, 116–119, 120, 121, 125, 140, 142, 186
- full 3D, 16, 19, 20, 22, 32, 140, 146, 223
defined, 16
- full-waveform inversion, 131–132, 207
- Galperin 3C geophone arrangement, 197
- gap in shot line, effect on migration, 291
- gaps in coverage, 125, 160, 178, 186, 192, 288, 290, 291
- gas chimney, 132, 144, 169, 189, 207, 209
- gas cloud, 202, 209
- Gaussian distribution, 68
- Gaussian (wavelet), 251, 252
- geometric series, 11
- geometry comparisons, 21–25, 40–41, 60–61, 90–92, 93, 94, 134–138, 208–216, 223
 areal versus orthogonal, 40–41, 60–61, 93, 223
 hybrid versus orthogonal, 94
 minimal data sets, 21–22, 23–25, 92–93, 208–216
 parallel versus orthogonal, 90–91, 119, 223
 slanted versus orthogonal, 92, 134–138
 zigzag versus orthogonal, 27, 91–92
- geometry imprint, 92, 117, 140, 144–146, 193 (*see also* acquisition footprint)
 dependent on sailing direction, 151–159
 periodic or systematic variation, 146
 reduction by center-spread streamer acquisition, 159

- geometry repeatability, 200, 201, 202, 203
 measure, 200
- geophone group centers, and positioning of sources, 1
- geophones, practical aspects, 65
- geophysical requirements, 87, 88, 95, 96, 114, 134, 219
- ghost effect, 161–167, 204
 first notch, 162, 163, 165, 166
- ghost-free pressure wavefield, 167
- ghost notches, 167, 190
- ghost response, 162
- graben, 170
- ground roll, 7, 15, 34, 35, 38, 39, 48, 50, 59, 60, 65, 69, 81, 89, 93, 99,
 102, 128, 229, 230, 242, 261, 294
 aliased, 7, 48
 analysis, 230, 231
 deep charges and shallow charges, 69, 128
 removal from minimal data sets, 38, 39, 48, 60
 scattered, 60, 133
 suppression in acquisition, 7, 15, 38, 39, 65, 69, 101
 suppression in processing, 1, 15, 48, 50, 60, 65, 85, 91, 93, 101
 velocity, 5, 6, 50, 59–67, 77, 93, 100, 258
- ground-roll cone, 38, 59, 60, 229, 230, 232
- Gulf of Mexico, 149, 172, 175, 177, 178, 196, 203
- Gullfaks field, 188
- Gunashli field, Caspian Sea, 94
- half-offset, and half-offset vector **h**, 1, 2, 19, 20, 41, 42, 46, 264, 265
- Hammersley points, 140
- “hands-off” seismic data acquisition, 15
- hexagonal sampling, 34, 40, 41, 196, 197, 295
 and signal-processing operators, 41
 effect on unit cell, 28
 efficiency, 40, 295
- HFVS (high-fidelity vibratory seismic) technique, 100, 129, 132
- high-resolution experiment, 131
- high-resolution survey, 118, 125, 149, 163, 197, 245
- Hild field, North Sea, 94
- history of 3D data acquisition, 16–19
- horizon attribute map, 121, 241
 amplitude, 159, 168, 241, 268 (*see also* horizon slice)
- horizon slice, 56, 144, 155, 156, 157, 160, 210, 211, 267, 278, 279, 280,
 281, 282, 285, 288
 display of, 156, 157, 212, 213, 222, 278, 280–282, 286–290
 for MDSs, 212, 213, 279, 280
- horizontal geology, 22, 36
- horizontal pulse distortion, 251, 253
- horizontal resolution, 88, 96, 98, 99, 250, 251, 253, 254, 255, 260, 261,
 278, 301
- hybrid gather, 55
- hybrid geometry, 16, 19, 90, 94, 117, 192, 194, 227
 and 3D receiver gathers, 94, 227
 in OBC acquisition, 187, 192, 194, 195
- hydrophone array, 149, 161, 187, 188, 197
- hydrophone and geophone at same receiver position (*see* dual sensor)
- hydrophones and geophones in same survey, 132, 197, 235
- hydrophones in land survey, 126, 197
- ideal parallel geometry, 20, 22, 35, 36, 41, 43, 146, 221, 266
 defined, 22, 35
- ideal 3D geometry, 16
- illumination analysis, 139, 285–289
- illumination area, 30, 31, 42, 125, 139, 159, 209–213, 220–227, 242, 278,
 285–289
- illumination capability, 139, 140 (*see also* imaging capability)
- illumination density, 30, 152, 210, 221
- illumination display, 238, 241
- illumination fold, 28, 30, 31, 43, 209, 210, 220–226
 defined, 30
 number of hits per bin, 30, 139, 210
- illumination gaps/holes, 154, 160, 221, 285, 289
- illumination, irregular, 90, 143, 151–159, 207, 220, 223, 281
- image area, 31, 242, 246, 280
- image area of PS-data, 210–212, 222, 225, 226
 clean image area, 225–226
- image fold, 28, 30, 31, 34, 210, 222, 226, 244, 283
 defined, 30
- image point, 31, 155, 211, 212, 275, 282, 283
- imaging capability, 30, 90, 172, 210 (*see also* illumination capability)
- imaging, two-step process, 211, 273, 274
- implementing the nominal geometry, 113–133, 191–192
- impulsive source/wavelet, 127, 128, 130, 132
- independent simultaneous sweeping, 132, 133
- Indonesia, 181
- infill shooting, 139, 149, 160, 172
 reduction of, 160
- inline bin size (*see* bin size)
- inline fold, 29, 30, 32, 33, 82, 88, 112, 113, 117, 120, 122, 149, 173, 174,
 175, 178, 180, 222, 237, 302
- inline roll, 26, 113, 114, 192, 193
- input gathers and prestack processing, 47–57
 amplitude variation with azimuth, 57
 amplitude variation with offset, 55–57
 first-break picking, 51–52
 interpolation and regularization, 50–51
 multiple suppression, 54–55
 muting, 51
 nearest-neighbor correlations, 52
 noise removal, 48–50
 residual statics, 52
 velocity analysis, 52–54
- interference noise, 132, 133
- interpolation,
 and regularization, 7, 34, 48, 50–51, 185, 204
 beyond Nyquist, 104
 crossline, 167, 169, 178, 184, 185, 203, 204
- intra-array statics, 7, 68, 69, 101, 103, 229
 formula, 68
- inverse Fourier transform, 51
- inversion, 10, 19, 59, 90, 131, 247, 248
 full waveform, 131–132, 207
- inverted zigzag, 18
- irregular illumination, 90, 143, 155, 207, 220, 223, 281
 of MS/MS acquisition, 90, 143, 155, 281
 of PS-wave acquisition, 207, 220, 223
- IsoMetrix, 167
- ISS (independent simultaneous sweeping), 132, 133
- jittered sampling, 140
- joint inversion, 90
- Kirchhoff integral, 303
- Kirchhoff integration, 140, 272
- Kirchhoff migration, 272
- k_x - k_y diagram/spectrum, 118, 140, 141
- k_x - k_y domain, 118, 256
- largest minimum offset, 32, 48, 234 (*see also* LMOS)
- laser interferometry, 16
- life-of-field seismic (LoFS), 19, 94, 195, 201, 202
- linear array, 65 (*see also* array)
 defined, 65
 orientation, 72, 76, 77
- linear-noise suppression, 50, 76, 77, 80, 83, 91, 94, 195
- line geometries, 16, 17, 18, 23, 35–39
 basic subset, 23
 crossed-array geometries, 16, 25, 28, 32, 33, 41, 92, 93, 180, 209
 orthogonal geometry, 36–39
 parallel geometry, 16, 17, 35–36
 sampling, 35–39
 slanted geometry, 16, 17
 spatial discontinuity, 34
 zigzag geometry, 17, 18, 39

- line intervals/spacings, 110–111, 139
 acquisition footprint, 118, 140–141
 adapt to shallow subsurface requirements, 89, 95, 110, 134
 adapt to target levels, 110, 241
 and crossline binsize in parallel geometry, 35, 36, 90, 192
 and other geometry parameters, 112, 113
 area of unit cell, 28–29
 aspect ratio, 33, 37, 38, 119
 fold, 28, 30, 38, 107, 110
 fold-taper zone, 121–122
 formula, 111, 302
 in real data, 108, 119, 120, 193, 241
 in synthetic data, 64, 82, 220, 222, 278, 283
 modeling, 139
 multiple of station interval, 88, 111
 offset sampling in bins, 33
 of low-fold data, 246
 pilot survey, 134
 reduction for better (scattered) noise suppression, 77, 78, 89
 rolling of template, 26, 113
 sparsity of geometry, 34, 110, 220
 spatial (dis)continuity, 53, 142, 220, 288, 290
- line turns in streamer acquisition, 146, 147, 181, 182, 185, 186
 lithology and pore-fill prediction, 144, 207
 LMOS (largest minimum offset), 32, 33, 37, 38, 40, 47, 48, 88, 92, 108, 110, 111, 234, 235, 237, 302
 and effective fold at shallow levels, 37, 110
 and OVT, 47
 dependence on type of crossed-array geometry, 92, 235
 square versus rectangular unit cell, 38
- LoFS (*see* life-of-field seismic)
 long offsets, reasons for use of, 111–112
 lowfold data, prestack migration, 241–246
 lowfold data examples, 229–246
 Nigeria 3D test geometry, results, 234–241
 3D microspread, 229–234
 lowfold data for reconnaissance 3D surveys, 246
 lowfold migration results, 244–246
 low frequencies, 76, 96, 128, 131–132, 163, 164, 165, 167
 loss of, ghost effect, 163
 the need for, 131–132
- low-velocity noise, 5, 40, 48, 59–65, 70–77, 103, 149, 190, 294
 and adequate sampling interval, 5, 40
 direct waves, 59
 effect of field arrays, 59, 65–68, 70–77
 properties, 59–65
 sampling, 103, 294
 scattered waves, 59–65
 Stoneley waves, 190
 suppression, 48, 59, 103
- Mad Dog, 172
 magnetotellurics, 111
 marine seismic data acquisition, 18, 19, 143–205
 air-gun arrays, 144
 geometry imprint, 144–146
 stationary-receiver techniques, 187–197
 streamer acquisition, 146–187
 time interval between shots and source strength, 198
 time-lapse acquisition, 198–204
- marine streamer geometry, inline and crossline fold, 29
 maximum crossline offset (*see also* maximum inline offset)
 in full-swath roll, 117, 119
 in multiline roll, 121
 in zigzag WATS, 185, 186
 narrow geometry, 71
- maximum dip (angle), 89, 96, 98, 99, 102, 123, 134, 160, 251, 301
 maximum frequency f_{\max} , 96–98
 achievable, 96
 and (required) resolution, 89, 96–98, 100, 248, 250, 260, 261, 301
 and sampling interval, 2, 91, 103, 149, 227, 293
 effect of array, 69, 101
 effect of attenuation, 217
 effect of ghost, 161, 162, 166
 effect of stretch, 105
 linked to maximum wavenumber, 5, 96, 97, 249
 of noise, 6, 65, 66
- maximum inline offset, 26, 32, 40, 92, 106, 112, 113, 176, 229, 232, 283, 284, 302
 and aspect ratio, 33, 112, 237
 in OBC acquisition, 193
 in orthogonal geometry, 26, 33, 36, 38, 40, 84
 in parallel geometry, 33, 148, 151, 152, 178
 in PS-data acquisition, 212, 222, 226
 in zigzag geometry, 27, 28, 39
 one of six geometry parameters, 33, 88, 114
 requirement for regular fold, 29, 88
- maximum minimum offset, 48, 88, 302 (*see also* LMOS)
 maximum offset, 27, 34, 38, 40, 107, 111, 139, 177, 302
 and deepest target, 37, 96, 107, 111
 and modeling, 139
 and streamer acquisition, 160–161, 171, 182, 185
 as function of traveltime, 104, 108
 as geophysical requirement, 88, 108, 111
 center-spread acquisition, 34
 determine, 111–112
 in relation to other geometry parameters, 112, 139
 in x or y , 34, 40, 178, 285
 of geometry, 27, 34
 smaller for structural analysis than for AVO analysis and velocity determination, 107, 111–112
- maximum stretch factor, 89, 96, 104–107, 301
 maximum unaliased frequency, 94, 149, 163, 164, 294
defined, 294
 maximum useful offset, 25, 27, 35, 36, 39, 106, 176, 280
 maximum wavenumber, 2, 5, 66, 70, 96–98, 101, 103–104, 230, 248–256, 293
 and geology, 103–104
 and resolution, 96–98, 248–256
 and spatial sampling interval, 2, 5, 103–104, 230, 293
 link with maximum frequency, 96–97, 101
 of noise, array design, 66, 70
- MAZ (*see* multiazimuth acquisition)
 MDS (*see* minimal data sets)
 megabin geometry, 16, 34, 35
 MEMS (microelectromechanical system) technique, 101
 merging, 3D surveys with same geometry parameters, 45, 114, 115
 Messinian unconformity, 170
 microspread (*see* 3D microspread)
 Middle East, 54, 82
 and high surface velocities, 54
- midpoint area, 21, 45–47, 55, 121, 125, 151, 174, 175, 255, 256, 277, 285, 287, 288, 291
 and illumination area, 31, 242
 and PS-illumination area, 209, 210, 220
 cross-spread, 21, 26, 27, 29, 30, 31, 36, 88, 92, 108, 230, 238, 243, 281
 cross-spread versus 3D shot, 17
 template, 27
 3D shot/receiver, 21
 3D subset/MDS, 23, 208, 209, 211, 255, 279
 zig-spread, 27, 28, 92
- midpoint/bin smear, 32, 124, 268, 269
 midpoint centering, 32, 125
 midpoint footprint of acquisition configuration, 181
 midpoint lines, 19–21, 23, 25, 35, 94, 145, 147, 175, 221, 266, 280
 and crossline bin size, 32, 33, 36, 147, 173, 175
 and crossline offset variation, 147, 154, 155
 in OBC acquisition, 221
 number of, in MS/MS acquisition, 146
 of adjacent boat passes, 148
- midpoint/offset coordinate system, 1, –4, 19, 201

- midpoint/offset wavenumber domain, 11, 12, 13
midpoint sampling, 260-261
migration, 271-291 (*see also* prestack migration)
 basics, 271-275
 purpose, 271-272
 truncation effect, 243, 275-277
 two-step process, 211, 242, 257, 273, 279
migration aperture, 98, 102, 108, 122, 248, 250-254, 257, 260-261, 274-276 (*see also* migration radius)
 and maximum dip, 102
 and resolution, 98, 248, 250-254, 257, 260-261
 and sampling interval, 102
 asymmetric, 254
 test, 122
migration apron (*see* migration rim)
migration artifacts (*see* migration noise)
migration-corrected gather, 273 (*see also* diffraction-flattened gather)
migration distance, 56, 123, 272, 277
 determination of, 123
migration noise/artifacts, 25, 38, 43, 50, 53, 102, 171, 178, 220, 257-258, 259, 261, 288-291 (*see also* migration smiles)
 acquisition strategies, 121, 123-125, 142, 155, 177, 259
 and random sampling, 140, 247
 and sampling, 34, 108, 110, 174, 176, 180, 225, 257, 261, 274
 phantom horizon, 155, 160, 178, 288, 290, 291
migration operator aliasing, 91, 102, 155, 173, 274, 288
migration radius, 121, 122, 123, 250, 251, 273-278, 301 (*see also* migration aperture)
migration rim, 87, 89, 99, 121-122, 277
migration smiles, 25, 154, 155, 160, 170, 178, 234, 281, 285, 288, 291
migration stretch factor, 251
migration stretch limit, 251
migration-velocity analysis, 174, 271, 281, 282, 285
Milan, Italy, random geometry, 19
minimal data sets (MDS), 25, 30, 31, 41, 207, 212
 basic subset of common geometries, 134
 common feature of all, 41
 comparison of sampled MDSs, 92, 93
 defined, 25, 125
 DMO, 263-269
 extent, 25, 41
 horizon slices, 279, 280
 ideal, 151, 261, 271
 illumination and imaging of PS-data, 208-212
 illumination area 30
 image area, 30,31
 imaging edge effects, 211-213, 225
 midpoint area and illumination area, 31
 migration of, 25, 241, 272, 278-279
 pseudo-COV gathers, 41
 PS-wave survey design, 219
 resolution of PS-data, 212-218
 resolution properties, 99, 248-256, 260
 sampling, 25, 41, 57
 scatterer behavior, 60-64
 useful in ray tracing, 139
 wavenumber coverages, and resolution, 212, 213, 216, 255, 256
minimum aperture, 274
minimum apparent velocity, 5, 65, 68, 100, 102, 225
minimum apparent signal velocity, 5, 6, 65
minimum-maximum offset, 47, 48, 88, 111, 302
 formula, 111
minimum resolvable distance/time interval, 96-97, 248, 250-253, 260, 261
 formula, 250, 301
mirror migration/imaging, 167, 196, 197
mispicks in time-shift analysis for statics, 52
missing traces, and migration artifacts, 50, 288, 290, 291
mixing in processing, 7, 9, 38, 66, 68, 267
 definition, 38
model-based noise analysis, 77-78, 109, 190
model-based survey design, 134, 139-140, 172
modeling, 95, 123, 134, 139, 140, 232, 225, 226, 257, 260, 275-276
 and sampling, 257
 complex geology, 134
 edge effects, 225, 226
 Fresnel zone and ZOI, 275-276
 irregular geometry, 139
 line intervals, 139
 maximum migration distance, 123
 maximum offset, 139
 physical, 260
 PS-wave imaging requirements, 226
 ray-based, 95, 101
 subsurface illumination, 134
 3D finite difference, 139-140
monitor survey, 196, 198, 199, 200, 203, 204
MS/MS (*see* multisource multistreamer)
multiazimuth acquisition (MAZ), 79, 143, 146, 159, 169-172, 180, 181
 uplift explained, 171
 why needed, 170
multiazimuth tomography, 171
multicomponent marine data acquisition, 196, 207 (*see also* 4C and dual-sensor technique)
multicomponent streamer, 161, 164-167, 188
multifold data, 16, 23, 241
multiline roll, 114, 116, 119-121, 134, 137, 138, 142
multiple aliasing, 80-82, 149
multiple suppression, 37, 54-55, 59, 77-84, 91, 111, 172, 180, 188, 195
 and aspect ratio of geometry, 84
 based on velocity discrimination, and stacking, 37, 77-84, 91
 in cross-spread domain versus in CMP domain, 54-55
 offset weighting, 79, 84, 91, 172
 processing techniques, 77-79, 172, 195
 τ - p algorithms, 54
 unit-cell-sized supergather, 55
multiplicity, 28, 303 (*see also* fold)
multisource multistreamer (MS/MS), 18, 36, 41, 81, 143, 164, 204, 280 (*see also* streamer acquisition)
 and azimuthal anisotropy, 155, 158
 and DMO, 266
 and obstacles, 186
 configurations, 35, 36, 146, 147, 149, 152, 153, 186
 crossline-offset variation, 147-149,
 illumination effects, 151-155
 multiazimuth acquisition, 169-172
 prestack migration, 155-159
 reducing spatial discontinuity effects, 155, 159
 single source versus two sources, 149, 155
 wide-azimuth acquisition, 172-186
mute function, 37, 89, 96, 104-108, 111, 112
mute offset, 104-108, 119, 222, 237, 301, 302
 and line intervals, 110, 302
 and maximum stretch factor, 105, 106
 and PS-data, 222
 2D versus 3D, 107
mute time, 48, 51
muting, 51, 108, 178, 226
 in PS-data, 226
 OVT-based, 51
nanospread, 229
narrow-(azimuth) geometry, 90, 142, 172, 175, 177 (*see also* wide versus narrow)
 modeling, 140
 offset weighting, 79
narrow-azimuth towed-streamer acquisition (NATS), 146-169, 172, 204
 azimuthal anisotropy, 155
 OVTs, 151
 velocity determination, 171
natural bin size, 30, 31, 210, 258
near-surface multiples, 81
near-surface variations/effects, 51, 59, 90, 101, 103, 198, 199, 219, 232

- near-surface velocities, 59, 68
- nearest-neighbor correlations for first breaks and residual statics, 52, 53
- nearest neighbors for interpolation in DMO, 269
- nears, mids, fars, 55–56
- Netherlands, The, 123, 197, 229, 238, 263
- Nigeria, 234–241, 279
 - acquisition methods, 235, 236
 - delta survey, topography, 235
 - 3D test geometry, lowfold data, 234–241
- Nile delta, 170, 171
- NMO, normal moveout, 11, 22, 56, 57, 102, 273
- NMO correction, 2, 7, 50–53, 56, 57, 79, 80, 82, 102, 105, 106, 145, 235, 263–265, 267, 273
 - undersampling of multiples after, 79–81, 149
- NMO stretch, 37, 91, 92, 97–99, 105–107, 112, 218, 223, 251, 255
 - in PS-waves, with formula, 218
- NMO stretch factor (*see* stretch factor)
- NMO/stacking velocity, 58, 105, 202, 209
- “no-data” zones, 104
- node acquisition (*see* OBN)
 - definition, 144
- noise, main types of, 59
- noise removal, 13, 35, 48–50, 67, 68, 92, 94, 132, 143, 238 (*see also* noise suppression)
 - after simultaneous shooting, 132
 - and station spacings, 13, 94, 238
 - by combination of field array and velocity filtering, 67–68
 - by 3D velocity filtering, 48
- from marine streamer data, 143
- noise cone
 - direct wave, 38, 59, 60, 229, 230, 232
 - traveltime surface of scatterer, 25, 60, 61, 64, 77, 93
- noise spectrum, 5
- noise spread, 13, 89, 100, 229 (*see also* 3D microspread)
- noise suppression, 35, 38, 39, 59–85, 94, 139, 197 (*see also* coherent noise suppression)
 - estimating, 232, 233
 - low-velocity noise, properties, 59–65
 - PS-data, 212
 - shot and receiver arrays, 65–77
 - stack responses, 77–84, 91
 - with increasing fold, 94, 108, 109
- nominal geometry, 32, 87, 88, 89, 103, 113–133, 134, 142, 153, 192–194
 - implementing, 113–133, 192–194
- nonrepeatability, causes, 201–202
- nonseismic technique, 111
- Noordoostpolder, Zuiderzee, The Netherlands, 229
- normal moveout (*see* NMO)
- North Sea, 175, 186, 188, 201
- Norway, 149, 181, 187, 199
- Norwegian Sea, 171
- Nrms (normalized root mean square), 199–202
- Nyquist frequency f_N , 293, 294
- Nyquist-Shannon sampling theorem, 293
- Nyquist wavenumber k_N , 5, 6, 7, 67, 68, 103, 104, 149, 167, 231, 293
- OBC (ocean bottom cable) technique, 18, 19, 36, 44, 87, 94, 139, 144, 160, 165, 166, 172, 187, 188, 189, 190–195, 197, 202, 207, 221, 227
 - alternative to streamer acquisition, 188, 193, 202
 - areal geometry, 187, 219
 - buried cables, 195
 - compared to dual-hydrophone acquisition, 197
 - compared to OBN, 205, 218
 - dual sensor, 165, 187, 188, 190–191
 - hybrid geometry, 19, 94, 187, 192
 - implementation aspects, 191–195
 - orthogonal geometry, 18, 44, 87, 172, 187, 192, 193, 219
 - over/under source, 166
 - parallel geometry, 36, 187, 192, 219, 221, 280
 - repeatability, 203, 205
 - resolution, 188
 - vector fidelity, 189
 - water depth, 192
- objective of acquisition technique, 35, 132, 172, 173, 181
- objective of survey, 87–90, 96, 118, 134
- objective of survey design, 35, 234
- objective of time-lapse seismic data, 198
- OBN (ocean-bottom-node acquisition), 144, 160, 172, 187, 189, 190, 195–197, 202, 203, 204, 205, 207, 219, 223, 245
 - brands, 197
 - compared with WATS, 197
 - repeatability, 202, 203, 205
- OBN acquisition, advantage over OBC acquisition, 205, 218
- obstacles/obstructions, 18, 88, 89, 114, 123–127, 144, 167, 197
 - and streamers, 143, 186, 187, 188
 - in time lapse acquisition, 160, 201, 203
 - solution testing with attribute analysis, 134
 - undershooting of, 160
- ocean-bottom cable (*see* OBC)
- ocean-bottom seismometer (*see* OBN)
- odd/even effect, 7, 11, 144, 145
- off-end geometry, 35, 204 (*see also* end-on geometry)
- offset distribution, 40, 51, 87, 237
 - acquisition footprint, 140, 144–146
 - across bins, 33, 40, 51, 53, 81, 92, 140
 - and loss of resolution due to stretch, 106
 - areal WATS versus circular WATS, 183
 - in bin, 32, 33, 52, 53, 87, 91, 135–138
 - in 2D, 11, 15, 77
 - in zigzag geometry, 18, 27
 - regular, irregular, 77, 81, 82, 84, 139, 146
 - slanted versus orthogonal geometry, 92
 - wide versus narrow geometry, 33, 82, 106
- offset equal to depth, rule of thumb, 106
- offset-equals-depth curve, 106
- offset sampling, 77, 91, 92, 144–146, 149, 193, 234
- offset-vector-tile gather (*see* OVT gather)
- offset-vector tile (OVT), 28, 41–42, 281 (*see also* OVT)
- offset wavenumber, 4
- offset weighting, 37, 79, 84, 91, 172
- Oman, 19, 94
- Omni 3D imaging program, 210
- one/single-line roll, 26, 116, 117, 118, 120, 125, 135, 136, 142
- $\frac{1}{4}\lambda$ rule for resolution, 99
- onSeis, 130
- optimization of survey parameters, 88, 112, 113, 134
- orientation of acquisition lines in orthogonal geometry, 64, 221
- orthogonal geometry, 16, 17, 18, 20, 22, 29, 34, 36–39, 40, 87–138, 192, 194, 221, 223, 259
 - and areal geometry, equivalence conditions, 40
 - and AVO, 55–57
 - and arrays, 65–70
 - and cross-spread, 20, 22, 23, 26, 27, 223, 229–234
 - and prestack migration, 281–286
 - and scatterers, 59–65, 77, 78
 - acquisition footprint, 140
 - aspect ratios, 33, 36
 - binning, 31
 - complementary role of shots and receivers, 36
 - fold of, 29
 - in OBC acquisition, 192–194
 - in PS-wave acquisition, 209–216, 220–221
 - line intervals, 110–111
 - offset distribution, 53, 84, 140
 - OVTs and OVT gathers, 41–47
 - parameters, establishment of, 87–113
 - sampling, 36, 99–104
 - six parameters of, 88
 - symmetric sampling requirement, 36
 - unit cell, 28, 29, 32, 33, 51
- outgoing signal of vibrators, 128
- outgoing signal of air-gun arrays, 144

- overlap of boat passes/sail lines, 148, 157, 160, 178, 204
 full overlap, 160
- oversampling, 5, 39
- over/under acquisition, 161, 164, 165, 166, 167, 186, 188, 197
- over/under source, 164, 166, 167, 180
 example layout, 166
- OVT gather, 38, 43–48, 50–57, 150, 151, 220, 269, 271, 288 (*see also* pseudo-COV gather)
 advantages over absolute offset ranges, 53, 281
 and attribute analysis, 134
 and AVAz, 57
 and AVO, 56
 and C-wave data, 210, 220–226
 and diodic effect, 209
 and DMO, 53, 269
 and (ir)regular geometry, 48, 88, 117, 121, 178
 and maximum offset, 48, 111
 and periodicity of geometry, 151
 and pseudo-COV gathers, 43, 99
 and pseudo-minimal data set, 43
 and spatial continuity, 34, 43, 45, 51
 and statics, 52
 and streamer acquisition, 150–151
 and velocity analysis, 53,
 and WATS geometry, 174–177
 and wide-azimuth surveys, 43
 empty bins, filled by forward/inverse Fourier transforms, 51
 example in 64-fold geometry, 44–45
 generating OVT, 43, 47
 illumination and imaging with, 51, 53, 56, 57, 197, 271, 277,
 280–290
 reciprocal, 50, 53, 57, 176, 221, 225, 288, 290
- OVT (offset vector tile), 28, 34, 44–46 (*see also* OVT gather)
 and AVO, 56–57
 and DMO, 269
 and line intervals, 110
 and multiline roll geometry, 121
 and prestack migration, 282–286, 288–290
 and prestack processing, 48, 51–53
 in marine streamer acquisition, 151, 155, 157, 159, 174–178, 180,
 204
 in OBN acquisition, 197
 in PS-wave acquisition, 221, 224
 introduction, 41–42
 reciprocal (*see* reciprocal OVT)
 zig-spreads and slanted spreads, 92, 186
- P- and PS illumination areas, various MDSs, 211
- P- and PS-wave acquisition, differences, 217
- parallel geometry, 16, 17, 18, 20, 23, 32, 33, 35–36, 90–91, 192, 194, 209,
 219, 221, 223–227
 and acquisition footprint, 28
 and concentric circle shoot, compared, 95
 and land data acquisition, 36, 90, 119
 and midpoint line, 20, 21, 23, 35
 and MS/MS data acquisition, 36, 143–180, 266
 and OBC data acquisition, 36, 192
 and orthogonal geometry, compared, 90–91, 119
 and azimuthal anisotropy, 155
 aspect ratios, 33
 common-inline offset gather, 36, 151, 271
 crossline bin size, 32, 36, 149, 150, 176
 fold, 29
 ‘ideal’, 20, 22, 35, 36, 41, 221, 266
 offset distribution, 81
 OVT gathers, 151
 prestack migration, 280–281
 sampling, 35, 225
 shooting direction, 139, 157, 167–169
 unit cell, 28
 wide-azimuth acquisition, 172–180
- Paris basin, 229
- passband, wavenumber domain, 7
- patch layout, 192, 193
- peak frequency, 108, 109, 123, 220, 250–252, 302, 304, 305
- periodicity of geometry, 28, 118, 140, 151, 174, 177, 183, 186, 225
 crossline roll, 119, 140, 144, 145, 151, 155, 174, 177
 unit cell, 28, 32, 51, 146, 151, 174
- periodicity in offset distribution, 51, 71, 77, 80, 146
- permafrost, and static variations, 103
- perpendicular strings and feathered strings, 74
- Peru, 244
- phantom horizon, 155, 160, 178, 288, 290
 in marine streamer acquisition, 290
 in orthogonal geometry data, 290
- Philippines, 150
- pie slices, 57
- piezoelectric vibrator, 131, 203
- pilot survey, 110, 113, 134
- plane-dipping reflector, geometry of, 264
- plane wave, 70, 252, 293, 295
- plane-wave assumption for array response, 70, 71, 72
- platforms as obstructions in MS/MS acquisition, 18, 143, 160, 201
- polar plot of array response, 71–75
- polarization filtering, 101
- polarized waves, 190, 219
- positioning in marine data acquisition, 143, 164, 167, 168, 169, 178, 203
- poststack migration better than prestack migration, example, 290
- potential resolution, 91, 99, 248, 249, 255, 256, 258–261
- PP-wavenumber coverage, 216
- pressure sensor (hydrophone), 144, 164, 165, 166, 188
- prestack amplitude, 89
- prestack imaging, 34, 88 (*see also* prestack migration)
- prestack imaging tests, 283, 285–291
- prestack migration, 15, 25, 32, 55, 57, 110, 271–291
 after regularization, 51
 and AVO analysis, 55, 56
 and azimuthal analysis, 57
 and resolution, 247–261
 dependence on geometry, 91, 92, 121, 124
 edge effects, 220
 Fresnel zone and zone of influence, 160, 275–278
 help from nonseismic technique, 111
 migration basics, 271–275
 of low-fold data, 121, 241–246
 of minimal data sets, 25
 of orthogonal geometry data, 36
 of OVT gathers, 51, 57, 110, 176, 280–291
 synthetic data, experiments with, 278–290
- prestack processing, 32, 47–58
 amplitude variation with azimuth, 57, 58
 amplitude variation with offset, 55–57, 199
 dependence on geometry, 91, 94, 139
 first-break picking, 51–52
 interpolation and regularization, 50–51, 134
 multiple suppression, 54–55, 92
 muting, 51
 nearest-neighbor correlations, 52
 noise removal, 35, 48–50, 88, 94, 109, 119, 233
 residual statics, 52
 velocity analysis and DMO, 52–54
 velocity filtering, 48
- prestack wavefield (*see* 3D prestack wavefield and 5D prestack wavefield)
- prism waves, 95, 168
- proper sampling (*see* alias-free sampling)
- pseudo-COV gathers, 34, 41–47, 51, 54, 155, 210, 220, 290 (*see also* OVT gather)
 construction of, 42–44
defined, 41
 determine maximum wavenumber, 97–99
 in MS/MS acquisition, 41, 155–156, 159

- prestack migration, 280, 281, 287
 regularization, 51, 290
 resolution, 261
 spatial discontinuity, measure of, 46–47
- PS-wave (*see also* converted wave)
 PS-wave acquisition, compared with P-wave acquisition, 226
 PS-wave data, 207
 asymmetry of raypaths, 208, 209, 226
 asymmetry in resolution when interchanging shot and receiver position, 213, 215
 diffraction flattening and ZOI, 211, 212, 214, 215
 diffraction-traveltime contours, 208
 illumination, 207, 209–210, 211
 illumination with multifold data, 220–226
 illumination with MDSs, 209–210, 211
 imaging with MDSs, edge effects, 210–212, 225–226
 NMO stretch, 218, 219
 properties in various MDSs, 208–216, 226
 reflection-traveltime contours in MDSs, 209
 requirement for crossline image fold, 222
 resolution, 212–218, 224, 227
 shear-wave splitting, 218–219, 225
 steepest events in shot and receiver gather, 226
 traveltime surfaces and apparent velocity, 208–209
 true-amplitude migration, 212
- PS-wave data and P-data, compared, 217, 218
 gas chimney, 144, 189, 207
 illumination, 209–210, 211
 loss of resolution due to absorption, 217, 218
 OVT gathers, 220–221, 226
 shallow and deep, 217, 218
- PS-wave illumination areas, 210, 211
 PS-wave imaging edge effect removal using clean-image area, 226
 PS-wave reflectivity, compared with PP-wave reflectivity, 217
 PS-wave 3D survey design, 219–225
 areal geometry, 223
 geometry comparison, 223–225
 modeling is recommended, 226
 orthogonal geometry, 220–221, 223–224
 parallel geometry, 221–224
 receiver lines oriented in dip direction, 221, 227
 sampling, 225
- PS-wavenumber coverage and resolution, 212–213, 216
 PS-waves, useful wavenumber range, 217
 pulse distortion in migration, 251, 253
 P-waves, loss of resolution due to absorption, 163, 164, 217
 pyramid, rounded, as traveltime surface, 60, 61, 76, 93
 PZ summation, 188
- Q*, quality factor, 163, 164, 166, 217, 218
defined, 163
- Qatar, 94, 100, 198
 Q-Land, 100
 Q-Marine streamer acquisition, 149, 161
 quad/quad (4/4) configuration, 145, 146, 154
 quad-sensor streamer, 166–167, 204
 quality of data (*see* data quality)
 quasi-Monte Carlo technique, 140, 247
 quasi-random sampling, 140, 247, 258, 261
- racetrack method, 146–148
 radar analysis, 60
 Radon transform, 78
 random geometries, 16, 19, 184, 185, 204
 random-noise suppression, 50, 77, 79, 80, 82, 109, 129, 130, 161, 258, 302
 random sampling, 7, 140, 225, 247, 258, 261
 compared with regular sampling, 247, 257–258
 ray-based modeling, salt model, 95
 Rayleigh criterion for resolution, 96, 97, 248, 250, 260, 301
 Rayleigh waves, 59, 67, 68, 101, 230, 231, 232
 ray tracing, 30, 97, 102, 123, 134, 139, 249, 251, 277
- RAZ, rich-azimuth acquisition, 180, 181, 186
 receiver-array response (*see* array response)
 recipe for 3D survey design, 88–89
 reciprocal OVTs, 34, 42, 45–46, 47, 117, 177, 193, 204, 220, 222, 285, 290
 and edge effects of cross-spreads, 45
 defined in cross-spread, 42, 45
 in areal geometry, 46, 47
 in C-wave acquisition, 220–222, 225
 in parallel geometry, 159, 175
 tilings, 46
 reciprocal OVT gather, 50, 53, 57, 176, 221, 225, 288, 290
 reciprocal traces, 32, 126, 127, 209
 reciprocity, P-wave-down/S-wave-up raypath, 209
 reciprocity theorem, 5, 7, 11, 16, 45, 127, 185, 209
 consequences of, 5
 redatuming, 90
 redundancy in multifold acquisition, 16, 56, 260
 redundancy in time-shift correlations, 52
 redundancy of short offsets in multiazimuth acquisition, 172, 181
 redundant shots and receivers for better processing results, 125
 reflection angle, 69, 70, 98, 106, 107, 112, 215, 218, 251, 301
 and array response, 69, 70
 and AVO, 107, 112, 169
 and NMO stretch factor, 106, 218, 251, 301
 and maximum wavenumber, 98, 251
 PP- and PS-data compared, 215
 reflection traveltime (*see* traveltime contour/surface)
 refracted P-waves, 67, 68
 refracted shear waves, 59, 67, 68, 230
 regularization workflow, 51
 regular fold, 29, 32, 117, 124, 125, 220, 302
 AVO, 55, 56
 requirement, 29
 obstacles, 124, 125
 regular (orthogonal) geometry, 27, 28, 31, 32, 33, 34, 44, 45, 51, 53, 77, 87, 88, 112, 114, 119, 139, 176, 177, 184, 193, 220, 281, 288
 conditions, requirements, 32, 88
 importance, 31, 34, 88, 176, 177, 288
 six parameters, 88
 2D, 77
 repeatability or nonrepeatability, time-lapse, 160, 188, 195, 198–204
 causes of nonrepeatability, 201–202
 measures of, 199–201
 sensitivity to shot and receiver locations illustrated, 201
 ways to improve, repeatability, 202–204
 representative velocity function, 89, 96, 102, 104, 105, 123
 to determine maximum migration distance, 123
 to determine mute function, 104, 105
 to determine radius of ZOI, 123
 to determine sampling interval, 102
 reservoir characterization, 10, 89, 90
 reservoir monitoring, 144, 198, 199, 207
 reshoots, 35, 104
 residual moveout, 53, 58
 residual statics, 52, 53, 238
 resolution, 96, 99, 213, 227, 247–261 (*see also* spatial resolution)
 achievable, 96, 99, 149, 248, 259–261
 achievable, *defined*, 248
 and array length, 129
 and dip direction, 227
 and fold, 108, 259–260
 and intra-array statics, 68
 and irregular illumination, 155
 and maximum frequency, 89, 96–100
 and migration aperture, 252–254
 and minimal data sets, 255–256
 and NMO stretch effect, 92, 97, 99, 105, 106, 107, 111, 251
 and sampling, 94, 99, 100, 149, 150, 171, 247, 257–260
 and streamers versus stationary receivers, 188
 and tow depth, 163, 164

- and unit cell, 261
 - areal geometry, 94, 223
 - at depth, array-based acquisition, 101
 - average, 99, 106, 256, 259, 301
 - coarse sampling worse than fine sampling, 247, 257
 - comparisons of width of spatial wavelet, 252–257
 - difference in shape of horizontal and vertical image, 252, 260
 - envelope for comparing horizontal and vertical resolution, 254, 260
 - formulas, 97, 98, 248–251, 301
 - limits, 149, 249, 250, 255, 260, 261
 - model experiments, 247, 251–259
 - potential, 91, 99, 248, 249, 255, 256, 258–261
 - potential, *defined*, 248
 - Rayleigh criterion, 96, 97, 248, 250, 260, 301
 - requirements, 89, 96–99, 100
 - temporal, 248, 250
 - theory of, 248, 249
 - vertical and horizontal, 88, 96, 98, 99, 250–255, 260, 261, 278, 301
 - resolvability of close events, 96, 247, 248, 259, 260
 - reverberations, 188, 191, 198
 - ρV , acoustic impedance (*see* acoustic impedance)
 - Ricker wavelet, 78, 99, 108, 123, 220, 250–252, 260, 302, 304
 - and bell-shaped wavelet, 260
 - and Gaussian function as image of diffractor, 251
 - rock-property analysis, 198, 207
 - rolling (*see* inline roll or crossline roll)
 - rolling during OBN acquisition, 196
 - Rotterdam Harbor, 12-fold survey, 197
 - ROV, remotely operated vehicle, 144, 188, 196, 207
 - rule of thumb, 48, 106, 108, 301
- Sacramento Basin, California, 18
- sail line, 28, 29, 147, 157, 183, 204, 227 (*see also* boat pass)
- salt domes, 18, 95, 111, 134, 168, 181
 - and line intervals, 111, 134
 - raypaths, 95, 139, 160, 168, 169, 170
 - target-oriented geometry, 95, 181
- salt flank, 95, 139, 168, 169, 170
- salt overhang, 95, 171
- salt pillow, 160, 170
- sampling, 32–41, 163, 257–258, 271, 293–295
 - and aliasing, 293–295
 - and unit cell, 32–33
 - coarse (*see* coarse sampling)
 - dense (*see* dense sampling)
 - migration noise test, 258
 - quasi-random, and migration noise, 258
 - symmetric, 3D, 34–35 (*see also* 3D symmetric sampling)
- sampling and aliasing, introduction, 293–295
 - illustrated, 294
 - f - k domain, 294
- sampling density, 85, 140, 258
- sampling interval, spatial, 2, 5–9, 31–41, 65, 99–104, 225, 258
 - adequate, 5–7, 13, 35, 40, 99, 100
 - and migration noise, 257, 258
 - basic, 5, 6, 35, 40, 65, 99–101, 103
 - basic signal, 6, 9, 35, 40, 65, 91, 99–101, 103
 - discussion of choice, 103
 - event-oriented, 99, 102
 - formula, 5, 100, 301
- sampling theorem, 293, 295
 - N-dimensional, 40, 295
 - Shannon, 293, 295
- sand dunes, 90, 103
- scattered wave, 5, 59–72, 76–78, 89, 93, 133, 189, 190, 232, 233, 257
 - apex area in cross-spread, 60–64, 72, 76–78
 - energy in apex area, 63, 64
 - line scatterer, 64–67
 - point scatterer, 59–64, 93, 257
 - suppression by field arrays, 70–72, 76, 77, 133
 - suppression by 3D filtering and fold, 77, 78, 93
 - in seafloor, 190, 191
- S/D (signal-to-distortion ratio), 200
- seabed noise, 189–191
- seisloop method, 19
- Seismic Wavefield Sampling*, 1, 34
- SEIS system (synchronized electronic impulsive source), 130
- semblance analysis, 52
- Seria field, Brunei, 197
- shadow zone, 31
- Shannon sampling theorem, 293, 295
- shear energy, absorption at seafloor, 218
- shear waves, polarization by fracture systems, 218–219
- shear-wave splitting, 218–219, 225
- shooting direction, 139, 143, 144, 146, 154, 167–170
- shooting downdip and updip, 151, 152, 156, 281
 - movement of reflection points, 152
- shot and receiver arrays, 2D data acquisition, 7–13, 15
- shot and receiver arrays, 3D data acquisition, (*see* array, field array)
- shot array, needed as much as receiver array, 7, 11, 12, 38
- shot-array response (*see* array response)
- shot density, 30, 112, 113
- shot interval and required streamer speed, 149
- shot/receiver coordinate system, 1–3, 19, 201
- shot repeat factor, 117, 118, 193, 195, 196
- shot salvo, 26, 27, 113, 116, 117, 119, 120
- shot spread (length), 29, 48, 111, 113, 194
 - defined*, 111
- shot strength, 10, 39 (*see also* source strength)
 - effect of previous shot, 198
- side lobes in array response, 66, 67, 161
- side lobes in seismic wavelet, 247–248
- side lobes in spatial wavelet caused by zero amplitude at $k_x = 0$, 253, 254
- side-scattered/side-swipe energy, 77, 109, 244
- signal cone, 6, 76
- signal spectrum, 5, 109
- signal strength, formula for, 303
- signal-to-ambient-noise ratio, 129
- signal-to-distortion ratio, 200
- signal-to-noise ratio (S/N), 2, 16, 89, 140, 161, 223, 245, 301, 303
 - and AVO analysis, 56
 - and fold, 16, 107, 108, 122, 245
 - and line intervals, 139
 - and stratigraphic interpretation, 89
 - and time between shots, 198
 - and tow depth, 161
 - and trace density, 109
 - formula for vibrators, 129
 - in stack, 2
 - migration effect, 110, 121, 223
 - offset-dependent, 104
 - of low frequencies, 164
 - of VHC data, 188
 - repeating the source, 130, 132
 - source strength, 198
 - time interval between shots, 198
 - 2D versus 3D, 109, 301, 303–305
- signal-to-random-noise ratio, 130, 164
- simulation model, 199, 200
- simultaneous sources, 40, 95, 100, 120, 132, 133
 - distance separated, 40, 95, 120, 132, 133
 - independent, 132, 133
 - marine, 159, 175, 180, 186, 227
 - passive and active separation, 180
- sinc (wavelet), 96, 250, 269, 298, 299
 - array response, 298, 299
 - interpolation, 269
 - Rayleigh criterion, 96, 250
- singlefold data (introduced for...),
 - basic subsets, 25

- minimal data sets, 25
 - OVT gathers, 43
 - pseudo-COV gathers, 41
- singlefold imaging, 15, 25, 241–243, 245, 282, 283
 - OVT gathers, 283
 - singlefold OBN compared with 52-fold marine streamer, 245
 - tiling of cross-spreads, 282
- single-hole dynamite shooting, 9, 10, 69, 128, 235
- single-point acquisition, 13, 100, 101, 103
- single-sensor acquisition, 65, 68, 77, 101, 103, 142, 229–234
 - marine, 149, 161
- single-source acquisition, 68, 132, 229–234
- skidding and offsetting approach, 124
- slanted geometry, 16, 17, 22, 23, 92, 114, 141
 - and slanted spread, 23, 92
 - attributes, 134–138
 - relative to brick-wall geometry and orthogonal geometry, 92, 134, 141
- slanted spread, 3D subset, 20, 22, 23, 25, 48, 49, 92
 - features in common with zig- and zag-spread, 92
 - geometry effect on amplitude, 92
- slanted streamer, 167
- slip-sweep technique, 129, 130, 132
- slope tomography, 53
- smearing caused by spatial filter, 232
- smooth acquisition lines, 124–126
- S/N (*see* signal-to-noise ratio)
- snail gathers, 57
- Snell's law, 102, 208
- solitary shots, 34, 124, 142, 279
- source depth, 96, 128, 161–164
- source directivity, 149, 189
- source selection, 127–132, 197
- source strength, 109, 130, 198 (*see also* shot strength)
- source vessel drift, 192, 203
- source wavelet, 15, 19, 96, 127, 128, 161, 165, 189, 251, 275
 - and ghosting, 161, 165
 - and migration, 275, 278
 - and resolution, 248, 251, 252, 260, 261, 278
 - and ZOI, 211, 278, 283
 - frequency content, 15, 96, 261, 278
 - impulsive, 127, 128, 130, 132
 - measurement, 128, 129
 - non-directional, 189
 - side lobes, 247, 248, 253, 254
- sources, complementary, 132
- sources, general requirements for, 127, 189
- sources, positioning, and geophone group centers, 1, 32
- sparse geometry, 16, 21, 30, 40, 94, 175, 204, 221, 246
 - and random sampling, 140
 - and time-lapse strategy, 203
- sparsity of acquisition geometries, 34, 35, 87, 204, 224, 246
 - and image quality, 222, 290
 - and spatial continuity, 34, 220, 222, 288, 290
 - mitigated by reciprocal OVTs, 34, 46, 204, 285–289
- spatial aliasing (*see* aliasing)
- spatial antialias filters, and seismic field arrays, 7, 11, 35, 38, 39, 66, 72
- spatial continuity, 15, 27, 34, 36, 46, 58, 87–88, 92, 142, 240
 - and obstacles, 123–127
 - and COV gather, 47
 - and cross-spreads, 27, 36, 42, 52, 230
 - and OVTs, 34, 58, 134
 - and prestack imaging, 34
 - and regular geometry, 88
 - and proper sampling of at least two spatial coordinates, 87–88
 - defined*, 34
 - design criterion, 58
 - improved by NMO correction, 50–51
 - main acquisition parameters and, 34
 - maximizing, 35, 36
- spatial discontinuity, 25, 27, 34, 43, 45, 48, 52, 53, 55, 88, 108
 - and migration artifacts, 34, 50, 125, 142, 160, 174, 220
 - criteria for, 47
 - effect on illumination, 285
 - examples, 34
 - in brick-wall geometry, 234, 235
 - in cross-spread, 27, 43, 52
 - in full-swath roll with irregular crossline offset, 119
 - in multiline roll, 121, 142
 - in MS/MS configurations, 148, 151–160, 179, 204
 - in OVT gather, 34, 43, 45, 46, 47, 48, 53, 121, 261, 281, 285, 288
 - in PS-wave acquisition, 220
 - in skidding and offsetting, 124–126
 - measure of, 46–47
 - solitary shots, 34, 124, 142, 279
- spatial resolution, factors affecting, 247–261
- spatial resolution formulas, 248–251
 - formulas for constant velocity, 249–251
 - migration/inversion, link with, 248–249
- spatial resolution measurements, 251–260
- spatial resolution, minimum resolvable distance relative to maximum wavenumber, 248
- spatial resolution, theory of, reviewed, 247–248
- spatial sampling interval (*see* sampling interval)
- spatial wavelet, width, 247, 248, 252–257, 260
- specular point, 274, 275, 283, 285 (*see also* zone of stationary phase)
- spider diagrams, 33, 44, 183
- spiderweb geometry, and salt-dome delineation, 95
- spiral survey, 168
- spread length (receiver), 27, 28, 29, 32, 48, 111, 112, 113, 117, 186, 257
 - shot spread, 29, 48, 111, 113, 194
- square array, and convolution of linear arrays, 72
- square sampling, and hexagonal sampling, 40, 41
- SRME (surface-related multiple elimination technique), 78
- stack array, 1, 15
- stack response / operator, 11, 12, 18, 59, 77–85, 140, 257, 258, 274
 - and quality of acquisition geometry, 84–85
 - average, 81, 83, 84, 91
 - formulas, 77, 79, 80
 - multiple suppression, by stacking, 77–84
 - 3D, 80–84, 90, 91, 119, 234, 240
- staggered array, 72, 73, 120
- staggered geophones, 100
- staggered sampling, 258, 259, 261
- staggered shot lines, 18, 27, 117, 234, 235
- Statfjord field, 94
- statics, 231
 - and arrays, 68, 69, 101, 103, 229
 - and sampling interval, 7, 101, 103
 - computation, correction, 2, 7, 51, 52, 89, 90, 110, 117, 192, 238
 - coupling, 29, 90, 117
 - elevation, 68, 69, 117
 - picking, 47, 51, 52
 - refraction, 51, 52, 238
 - residual, 47, 52, 238
- static correction procedures, 2, 7, 51, 52
- stationary geometry, 122
- stationary phase (point /zone of), 243, 263, 264, 265, 266, 275, 277, 279, 288
- stationary-receiver techniques, 18, 40, 144, 146, 187–197
 - advantages over towed streamers, 187, 188, 204
 - coupling issues, 189
 - dual-sensor application, 190–191
 - history, 188–189
 - noise at sea bottom, 189–190
 - OBC, 191–195
 - ocean-bottom seismometers/nodes, 195–197
 - overview, 187
 - source array requirement, 189
 - transition-zone acquisition, 197

- station interval/spacing, 5–9, 31–41, 99–104 (*see also* sampling interval)
 - and fold in orthogonal geometry, 29–30
 - array length, 7–9, 65–69, 76, 101
 - aspect ratio, 33
 - bin fractionation, 258, 259
 - bins, 31
 - choosing its value, 99–104
 - in low-fold acquisition, 246
 - in real data, 9, 100, 101, 120, 140, 173, 193, 219, 230, 238
 - in synthetic data, 278, 283
 - line interval, 88, 111, 140
 - marine streamers, 149, 175
 - maximum inline and crossline offsets, 32
 - migration noise, 108
 - noise suppression, 103, 233
 - number of bins in unit cell, 32
 - preservation of high frequencies, 100–102
 - smaller is better, 13, 69, 142, 302
 - spread length, 28
 - statics, 68, 69, 103
- steerable sources, 203
- steerable streamers, 143, 160, 161, 164, 186, 203, 204
- steering for coverage, 160, 203
- Stoneley waves, 190, 191
- stratigraphic interpretation, 89
- streamer acquisition, 35, 146–186
 - crossline fold, 28, 29, 33, 148, 151, 157, 159, 171, 204
 - crossline-offset variation, 147–149
 - depth controllers, 149, 161
 - entangling, 149, 153, 161
 - hydrophone array, 149, 161
 - inline fold, 29, 149
 - inline bin size and crossline bin size, 149–150
 - maximum offset, 160–161
 - multiazimuth acquisition, 169–172
 - multicomponent streamer, 161, 164–167, 188
 - multisource multistreamer configurations, 146–147
 - narrow-azimuth acquisition, 146–169, 172, 209
 - offset-vector-tile gathers, streamer acquisition, 150–151
 - operational aspects, 186
 - over/under technique, 164
 - shooting direction, 167–169
 - source interval, number of sources, and fold, 149
 - sources and streamers, depth of, 161–164, 167
 - spatial discontinuity in marine streamer acquisition, effects, 151–160
 - variable-depth streamer, 167
 - wide-azimuth acquisition, 172–186
- streamer depth, 149, 161–164, 167, 186, 188
- streamer interval
 - and streamer steering, 160
 - crossline bin size, 36, 147, 149
 - crossline roll/midpoint range, 29, 148, 151, 171
 - in WATS acquisition, 173, 175, 177–180
- streamer steering (*see* steerable streamers)
- streamers, solid or fluid filled, 149, 161, 167
- stretch factor, 98, 104–107, 112, 218, 251, 301
 - average, 106, 107, 301
 - maximum, 89, 96, 104–107, 301
 - migration, 251
 - PS-wave data, 218
 - 2D data compared with 3D data, 106–107
- strike acquisition/shooting (*see* dip or strike acquisition/shooting)
- striping, causes, 50, 121, 144, 145, 160, 221
 - ambient noise, 50
 - crossline periodicity in offset distribution, 144, 145, 221
 - feathering, 144, 160
 - irregular orthogonal geometry, 121
 - poor receiver coupling, 50
- strum noise, 165
- subhorizontal geology, 101, 103, 104
- subsalt exploration, 95, 139, 172, 179, 180, 207
- subsurface diagram, 2, 3
- subsurface stacking chart, 3
- SUMIC technique, 144, 188, 189, 196, 207
- supergather, 55
- supershot gather, 178, 180
- superspread, 114, 120
- surface-consistent equalization, 10
- surface-consistent deconvolution, 238
- surface diagram, 2, 3
- surface ghost, 128, 203
- surface scatterer, 60
- surface stacking chart, 3
- surface wave, 5, 60, 62, 64, 129, 230 (*see also* ground roll)
- survey design, information needed, 89–90
- swath
 - in OBC acquisition, 192, 193, 196, 221, 223
 - in orthogonal geometry, 113, 114, 116, 117, 120
 - in parallel geometry, 36, 90, 146, 151, 157, 159, 173, 177, 178, 180, 183, 185, 203, 204, 221
 - in VHC acquisition, 188,
 - in zigzag geometry, 27, 114, 186
- sweep, 40, 95, 96, 100, 120, 128–134, 229
 - frequency range, 96, 129–131
 - HFVS, 100, 132
 - length, 128–130, 133
 - number of sweeps per shot point, 129–131, 133, 134
 - reliability, 130
 - slip-sweep, 129, 130, 132
 - upsweep, 128, 129
- swell noise, 149, 161
- symmetric sampling, 1, 4–10, 12, 13, 15, 16
 - advantage, 9, 10
 - and 2D surveys, 13
 - array-based, 7, 13
 - theory, 4, 5, 15
- symmetric sampling versus asymmetric sampling, 7, 9–10, 12, 13, 243
 - center-spread shooting, 9, 10
 - end-on shooting, 9
- target, depth/levels, 89
 - deep, and length of streamers, 146, 160
 - deep, and shot interval, 149, 173
 - deepest, and AVO, 107
 - deepest, and maximum offset, 35–37, 96, 106, 107, 109, 112, 160
 - deepest and radius of ZOI, 123, 304
 - determine maximum offset, 111–112
 - Fresnel zone for each, 160
 - geophysical requirements at each, 96
 - illumination, 88, 95, 238
 - interval velocity, 96, 102, 301
 - line interval, 110, 111, 237, 241
 - low relief, and upholes, 90
 - mute offset at each, 104
 - maximum dip angle at each, 99
 - parameter optimization, 112–113
 - required fold, 88, 89, 107–110, 246
 - required resolution, 89, 96–99
 - sampling interval, 99, 103, 134
 - shallow and near-surface conditions, 59, 96, 104, 110, 134, 139
 - shallowest, and line intervals, 37, 107, 134, 139
- target-oriented geometry, 18, 90, 95
- τ - p_x - p_y filtering, 94, 195
- Teal South 4C/4D test survey, 195
- teardrop problem, 148
- template, 26, 27, 92, 113, 114, 126, 135–138, 235, 236
 - aspect ratio, 26, 33
 - different implementations, same nominal geometry, 113, 114, 116–121
 - fold formula, 30
 - in OBC acquisition, 192

- in the presence of obstacles, 125, 126
- template rolling, 114
 - full-swath roll, 116, 117–119 (*see also* full-swath roll)
 - multiline roll, extra receiver lines, 116, 119–120
 - multiline roll, no extra receiver lines, 116, 120–121, 134, 137, 138, 142
 - one/single-line roll, 26, 116, 117, 118, 120, 125, 135, 136, 142
 - one-line roll, sources outside template, 116, 117
- terrain conditions, adapting to, 132, 197, 235
- testing as part of 3D survey design, 87, 113, 133–134
 - array parameters, 65, 76
 - box test, 133, 234
 - dealing with obstacles, 134
 - decimation tests using pilot survey, 110, 113, 134
 - energy tests, 129
 - geometry to be used, 133, 234–241
 - interval between shots, 198
 - lowfold data, 110
 - migration aperture, 122–123
 - modeling as alternative to field testing, 134, 139–140
 - pilot survey, test geometry, 134, 234–241
 - processing tests, 106
 - shot-hole depth, 128
 - source strength, 198
 - sweeps, 133–134
 - 3D microspread, 59, 133, 232–234
- 3C data acquisition, 95, 101, 189, 207, 219
- 3C geophone/sensor, 101, 144, 166, 167, 187, 189, 196
- 3D acquisition geometries, properties and sampling, 15–58
 - continuous wavefield, 19–31
 - continuous wavefield, sampling of, 31–42
 - prestack processing using most suitable subsets, 47–57
 - pseudo-COV gathers, 41–47
- 3D CMP, 20, 22, 23, 25, 209
- 3D common-receiver gathers, 16, 18, 20, 21, 40
 - PS-illumination and imaging, 209–212
 - traveltime contours in PS-wave, 208, 209
- 3D common-shot gather, 16, 20, 21, 23, 25, 40, 254
 - alias-free sampling, 40
 - properties, 21, 22
 - PS-illumination and imaging, 209–212
 - resolution, 254, 256, 261
 - traveltime contours, 23
 - traveltime contours in PS-wave, 208, 209
- 3D data, sampling requirements, similarity to 2D data, 103
- 3D finite-difference modeling, 139
- 3D (f - k) filtering, 36, 40, 48, 49, 50, 78, 91, 92, 101, 103, 238 (*see also* 3D velocity filter)
 - compared to cascaded filtering, 48, 49
- 3D f - xy filtering, 36
- 3D geometries, classes of, 16–19
- 3D geometries, stack responses, 80–84
- 3D geometry on land, guidelines for design, 87–142
 - acquisition footprint, 140
 - attribute analysis, 134–138
 - geometry, choice of, 90–96
 - geophysical requirements/constraints, 88
 - model-based survey design, 134, 139, 140
 - nominal geometry, implementation of, 113–133
 - parameters, selection of main, 96–113
 - preparations, 89–90
 - random sampling, 140–141
 - regular geometry, 88
 - spatial continuity, 87–88
 - survey design, recommendations, 141–142
 - test results, 234–241
 - testing, 133–134
 - 3D survey design, general recipe for, 88–89
- 3D marine streamer acquisition, 15, 146–186
- 3D microspread, 59, 133, 229–234 (*see also* noise spread)
 - layout, 230
 - useful in 3D survey design, 59, 133, 232–234
- 3D midpoint, 20, 22–23, 25, 209
- 3D prestack wavefield of 2D line, 1, 4, 6, 7, 9, 11
 - properties, 4, 5, 6
- 3D receiver gather (*see* 3D common-receiver gather)
- 3D shot gather (*see* 3D common-shot gather)
- 3D spatial bandwidth, 248
- 3D spatial resolution, 255–256
- 3D stack response, 80–84
- 3D Strathspey survey, North Sea, 188
- 3D subsets of 5D prestack wavefield, 19–22
 - COV gather, 20, 22
 - cross-spread, 20, 21–22
 - midpoint line, 19, 20, 21
 - slanted spread, 20, 22
 - 3D midpoint, 20, 22
 - 3D shot, 20, 21
 - 2D line, 21
 - zig-spread, 20, 22
- 3D subsets and acquisition geometry, 23–27
 - COV gather, 23–25
 - cross-spread, 23–27
 - extent, 25
 - fold, 25
 - maximum offset, 25
 - minimal data sets, 25, 31
 - role in 3D symmetric sampling, 34–41, 265, 319
 - spatial continuity, 34
 - 3D shot, 23–25
 - traveltime contours, 23–25
 - zig-spread, 23, 24, 27
- 3D survey design, fold requirement, 107–110, 303–305
- 3D survey design guidelines, 87–142
- 3D survey design, PS-waves, 219–225
 - geometry, choice of, 219–225
 - sampling, 225
- 3D survey design, general recipe for steps in, 89
- 3D symmetric sampling, 15, 34–35, 87
 - and basic subsets, 35, 57
 - and DMO, 263
 - and four spatial coordinates, 35
 - areal geometry, 40
 - areal WATS compared with, 176–178
 - aspect ratios, 88
 - orthogonal geometry, 36–39, 120
 - parallel geometry, 35
 - perfect example, 112, 120
 - requirements, 35
 - zigzag geometry, 39
- 3D/3C surveys, design of, 207
- 3D velocity filter, 48, 59, 60, 62–65, 67, 68, 76, 77, 85, 99, 233
 - examples of results, 49, 78
- thumper, 16, 130
- tidal variations, 197, 201
- tiling of cross-spreads, 42, 43, 281, 282, 287
- tiling of OVTs, 43, 46, 47, 48, 220, 221, 224, 269, 281
- tiling of reciprocal OVTs, 46
- tilted streamer, 167
- time interval between shots and source strength, 198
- time-lapse acquisition, 188, 198–204
- time-lapse seismic analysis, ground rule, 201
- time-lapse seismic data, and reservoir monitoring, 199
- time-shift measurements for statics determination, 52
- time shifts between array elements, 68
- time-shifts between baseline and monitor surveys, 200–202
- time slices, 51, 60, 77, 133, 140, 160, 170, 238, 242, 247, 283
 - acquisition footprint, 118, 141, 144, 154
 - after diffraction flattening, 243, 284
 - cross-spread, 18, 22, 36, 37, 50, 59, 230–232, 243
 - displays, 4, 22, 37, 50, 78, 118, 133, 141, 154, 171, 232
 - fold variation, 51

- k_x - k_y diagram, 118, 140
- 2D, 2–4
- tomography for velocity-model building, 53, 171, 174
- total fold, 29, 30, 37, 88, 104, 108, 112, 113, 120, 159, 173, 178, 180, 221
(*see also* full fold)
- total stack response, 11–13
- tow noise, 161, 167
- trace density (as function of offset), 37, 38, 55, 79, 84, 106, 183, 185, 237
- trace density (per unit area), 19, 37, 91, 94, 109, 112, 113, 180, 195, 197
- trace-vector diagrams, 33
- transition zone, 118, 144, 187, 197
- traveltime contour/surface,
 - apparent velocity, 60
 - apex areas, 64
 - diffraction, 24, 63, 91, 123, 242, 243, 248–251, 256, 257, 260, 261, 271–273, 275, 277, 279
 - diffraction-flattened reflection, 211, 214, 273, 278–279
 - dipping plane, 2, 24, 281–283
 - energy distribution of scatterers, 62–64
 - gradient, 60, 62, 64–66
 - in cross-spread, 23, 24, 37, 60, 61, 64–66, 93
 - in 3D shot, 60, 61, 64, 93
 - in 3D subsets, 23–25, 208, 209
 - in zig- and zag-spreads, 91
 - line scatterer, 64
 - multiple, 55
 - PS-waves, 208, 209
 - reflection, 22, 278, 279; scatterer, 60–64, 72, 93
- triple zigzag, 18
- true-amplitude migration, 25, 92, 157, 212, 248, 271, 280–282, 285, 288, 290
 - and acquisition footprints, 290
- tuning thickness, 250
- 2C, two-component (*see* dual sensor technique)
- 2D data combined with lowfold 3D data, 244–245
- 2D data, conventional, compared with lowfold 3D data, 245
- 2D data acquisition, best, 6
- 2D Fourier transform, 178
- 2D grid of lines with lowfold 3D, 108, 244–245
- 2D line, 2–4
 - offset as third dimension, 2
 - properties, 2–4
 - time slice, 2, 4
 - smoothness criterion for crooked lines, 124
- 2D noise spread, 229
- 2D over/under acquisition configuration, 164
- 2D stack response, 77, 79, 82, 84, 258
- 2D symmetric sampling, 1–13, 15, 34–35
 - requirements, 7, 35
 - symmetric sampling versus asymmetric sampling, 7, 9–10, 13
 - theory, and 3D symmetric sampling, 15
 - total stack response, 11–13
- two-trace running mix, 7, 66, 68
- TZ (transition-zone) surveys, 197
- umbilicals, 146
- undershooting, 18, 160, 186, 188
- undershooting and long offsets, 139, 160, 177
- undershooting of gas chimney, 169
- UniQ, 100
- unit cell, 28, 29, 32–34, 51, 53, 88, 121, 122
 - and acquisition footprint, 28, 51
 - and fold of geometry, 29, 30, 33, 51, 108, 183
 - and periodicity of geometry, 28, 32, 51, 225
 - area, as factor in resolution, 261
 - aspect ratio, 33, 34, 37, 178
 - AVO, 56
 - fullfold and fold-taper zone, 121, 122
 - LMOS, 32, 37, 38, 110
 - offset distribution, 32, 33, 46, 51, 53
 - OVTs, 38, 41–47, 151, 197, 282, 284
- updip move of reflection, 151, 152, 153, 159, 285
 - in migration, 242
 - in PS-wave, 209, 210
- updip versus downdip multiple behavior in cross-spread, 54
- updip versus downdip shooting, 9, 151, 152, 153, 155, 156, 159, 281
PS-wave, 226
- uphole surveys and statics determination, 90
- Valhall data, full-waveform inversion of, 132
- Valhall field, LoFS survey, 19, 94, 195, 201, 202
- variable-depth streamer, 161, 167, 188
- vector fidelity, 167, 189, 197
 - defined, 189
- vector infidelity, 189, 190
- vector representations, shot, receiver, midpoint, half-offset, 2
- velocity analysis, 16, 32, 52–54, 57, 107, 169, 174, 209, 271, 281, 282, 285, 288
 - difference horizontal and vertical velocity, 112
- velocity model-building, OVT gathers and slope tomography, 53
- velocity-model updating process, 271
- vertical pulse distortion, 251
- velocity sensor, particle, 144, 164, 165, 166, 188
- vertical resolution, 88, 96, 98, 99, 250, 251, 254, 255, 260, 261, 278, 301
- vertical seismic profiles (*see* VSP)
- vessel pass (*see* boat/vessel pass)
- V_{fast} - V_{slow} anisotropy analysis, 58
- VHC (vertical hydrophone cable) technique, 187, 188, 196
- vibrator, 27, 39, 91, 100, 120, 128–132
 - array, 69, 74, 120, 129, 140
 - ground force, 128, 129
 - group/fleet, 120, 129, 132, 140
 - history, 128, 129
 - marine, 144
 - mini, 203
 - single, 40, 93, 95, 140, 229, 230
 - sweep (*see* sweep)
- vibroseis, 117, 127, 128, 129, 130, 132, 197 (*see also* vibrator)
- V_p/V_s , 208–224, 226
 - effect on illumination area, 209–211
 - effect on illumination fold, 220–224
 - effect on image area, 210, 211
 - effect on NMO stretch, 218
 - effect on 3D survey design, 219, 226
 - effect on wavenumber coverage, 216
- VSP (vertical seismic profiling), 18, 247
 - acquisition, 18, 90, 95
 - processing of VHC data, 188
 - providing velocity for survey design, 90, 96, 112
 - repeatability analysis, 201, 202
 - resolution analysis, 249
- walkaway VSP, 188
- WARP (wide-angle refraction and reflection profiling), 195–196
- water temperature, and water velocity, 201, 202
- water velocity and maximum unaliased frequency, 94, 149
- WATS types
 - areal, 176–180, 183, 185, 186, 189, 204
 - circular, coil shooting, 181–185, 204
 - zigzag, 185–186, 189
- WATS, wide-azimuth towed-streamer acquisition, 19, 34, 92, 139, 142, 143, 146, 148, 170, 172–186, 188
 - characteristics, 172–174
 - compromises, 176–178
 - parallel or areal geometry, 175
 - with simultaneous shooting, 180
- WATS configurations, 172–180, 186
 - BP WATS, 173–178
 - crossline fold, 173–175, 178–180, 204
 - front and aft shots, 171, 179

- front shots only, 179
 inline fold, 173–175, 178, 180
 orthogonal WATS, 177
 RAZ, rich azimuth, 180–181, 186
 Shell WATS, 175, 177, 178
 WesternGeco WATS, 178, 179, 180
- wave equation, 94, 225
- wavelength, smallest, and basic sampling interval, 5
- wavelet, 70, 84, 96, 97, 165, 273, 302
 deghosted and ghosted, 164, 165
 difference between horizontal and vertical wavelet, 260
 frequency content, 84, 261, 275, 276
 length, 123, 211, 214, 277, 279, 283, 302, 304
 length and ZOI, 123, 211, 214, 277, 304
 migration edge effect on, 123
 Rayleigh criterion, 97
 reflection, diffraction and truncation, 275
 resolution and width of central lobe, 247, 248, 252–257
 Ricker (*see* Ricker wavelet)
 source (*see* source wavelet)
 spatial, 248, 252–258, 260
 stretch, 105, 253
 tuning thickness, 250
- wavenumbers and spatial coordinates, 2
- wavenumber coverage, 212, 213, 216, 217, 248, 255, 256
 mapping traveltimes surface to 3D wavenumber space, 248
- wavenumber spectrum, 3, 4, 40, 103, 104, 141, 251
- WAZ (*see* wide-azimuth acquisition)
- wedge model, 96–97
- weight-drop units, 127, 130
- weighted arrays, 7, 11, 70, 71, 297
- West Africa, 193
- wide (acquisition) geometry, 26, 33, 36, 37, 142, 235–241
 beneficial effects, 36, 37
 average stretch factor, 106, 107
 better diffracted multiple suppression, 37, 89, 170, 172
 better multiple suppression, 84, 91
 better prestack noise suppression, 59, 85, 109, 117
 common-offset-range gather, 52
 source directivity, 127
 taper zone, 121
- wide-azimuth acquisition (WAZ), 43, 54, 79, 90, 106, 139, 143, 181, 184,
 188, 189, 204, 207, 219, 224, 229, 263, 270 (*see also* wide
 (acquisition) geometry)
- wide-azimuth towed-streamer acquisition (*see* WATS)
- wide-azimuth swath (WAS) technique, 117
- wide versus narrow
 aspect ratio, 26, 33
 azimuth, 90
 bin offset distribution, 33
 choice of arrays, 77
 common-offset-range gather, 52, 53
 complex geology, 90, 139, 180
 DMO, 263
 feathering, 177
 fold buildup, 37, 237
 fold taper zone, 121
 implementation, 117
 multiple suppression, 84, 91
 Nigeria 3D test, 234–241
 NMO stretch effect, 223
 number of edges, 36, 142
 PS-wave processing, 224
 source directivity, 189
 spatial filtering, 110
 stack responses, 83, 85
 width of swath, 177
- Xinchang field, Sichuan Basin, fracture density, 219
- X-spread (cross-spread) technique, 16, 18
- zag-spread (*see* zig-spread)
- zero-offset
 and maximum frequency, 97
 and migration, 272, 277–280
 and migration distance, 123
 and PS-wave data, 208, 216, 218
 and resolution/NMO stretch, 97, 98, 104–105, 106, 111, 216, 218,
 249–256, 258, 259, 261
 and sampling, 99, 102
 section, 2
 time, 82, 105
- zig-spread, 20, 22, 23, 24, 27, 28, 186
 maximum inline and crossline offsets, 27, 28, 39
 OVT, 186
 properties, 24, 27, 28, 92, 93
 traveltimes contours, diffraction, and dipping plane, 23, 24, 91
- zigzag geometry, 16, 17, 18, 20, 22, 23, 27–28, 39, 91, 142
 and desert environment, 18, 39, 91
 and f - k filtering, 91
 and orthogonal geometry, compared, 27, 91
 and trace spacing in shot and receiver gathers, 39
 double zigzag, 18, 82, 83, 91
 efficiency in open areas, 91
 inverted zigzag, 18
 maximum crossline offset, 27, 39
 offset distribution, 81, 84
 sampling, 39, 92
 shot intervals, 27, 142
 stack response, 83, 84
 subsets of, 23, 27–28, 93
 template, 114
 triple zigzag, 18
- zigzag WATS, 185, 186, 189, 204
- zippers, 113–115, 120
- ZOI (zone of influence), 108, 123, 211, 212, 223, 271, 274, 275, 276–277,
 278, 290, 301, 303–305
 and Fresnel aperture, 303
 and Fresnel zone, 271, 276–277, 278, 290
 and wavelet length, 123, 211, 214, 277, 304
 determination of, 123
 radius, 108, 109, 123, 275–278, 301, 303–305
 offset dependency, 277
- zone of stationary phase, 243, 263, 265 (*see also* specular point)